

Economic H.264 DVR



Features

- Embedded Linux OS
- 4 Video Input/1 Video Output
- 4-ch Audio input/1-ch Audio output
- 4 Alarm input / 1 Alarm Relay Output
- VGA Output
- Support TCP/IP, DHCP
- Support Remote Software
- Support USB, Thumb Drive, External CD-RW or DVD+RW

ADR-2104

Specification

Model	ADR-2104
Video	
Video Compression	H.264
Preview Resolution	PAL: 352×288 ; NTSC: 352×240
Playback Resolution	CIF, 352×288 (PAL) 320×240 (NTSC) ; QCIF
Video Input	4CH BNC*4
Video Output	Composite video output: 1CH, BNC (Electrical Level: 1.0Vp-p, resistance: 75Ω)
	Spot video Output: 1CH, BNC (Electrical Level: 1.0Vp-p, resistance: 75Ω)
Frame rate	PAL:1/16 to 25FPS, NTSC: 1/16 to 30FPS
Stream type	Video/Video&Audio
Bit rate	32Kbps to 2Mbps, self-defined
Audio	
Audio input	1CH, RCA (Electrical Level: 2.0Vp-p, Resistance: 1KΩ)
Audio output	1CH, RCA (Linear Electrical Level, Resistance: 600Ω)
Alarm	
External alarm in	4
Relay output	1
Mechanical	
HDD interface	1 SATA interface can support 1 SATA HDD up to2000GB in total
Communication interface	1 RJ45 10M/100M self-adaptive Ethernet Interface 1 RS-485 interface
USB interface	1 USB interface, USB2.0
VGA interface	1 VGA interface can support resolution: 800×600/60Hz, 1024×768/60Hz, 1280 ×1024/60Hz
Voice talk	1 channel, RCA (Electrical Level: 2.0Vp-p, Resistance: 1KΩ)
Power Supply	12VDC
Power consumption	≤10W (without HDD)
Working temperature	-10°C ~ 55°C
Working Humidity	10% to 90%
Size	315×230×45 mm
Weight	< 8Kg (without HDD)