

Standalone DVR



Features

- H.264 Compression
- D1 Resolution
- 4CH Video Input
- Support VGA Output
- 4CH Audio In / 1CH Audio Out
- 4 Alarm In / 1 Alarm Out
- Support IE Remote monitor\control\setup\playback
- Support Protocol : TCP/IP,UDP,HTTP,NTP,DHCP,DDNS
- Support 1*RS485 Port for PTZ Function
- Support 1*SATA HDD
- Power adapter input AC100~240VAC output DC12V3A15A

ADR-2204

Specification

Model	ADR-2204
Video	
Compression	H.264
Video Input	4CH, BNC (1.0Vp-p,75ohm)
Video Output	1*BNC (1.0Vp-p,75ohm), 1*VGA(800*600, 1024*768)
Looping Output	---
Audio	
Audio Input	4 (D-SUB , Line-In)
Audio Output	1*RCA, Line-In (Linear electric level,Resistance:600Ω)
Recording	
Record Resolution	PAL:720*576 100PPS, NTSC:720*480 120PPS
Record Speed	PAL:100FPS,NTSC:120FPS
Record Mode	Continual\Schedule\Motion
Display Resolution	PAL:720*576 NTSC:720*480
HDD Interface	1*SATA HDD
Other	
Alarm Input	4
Alarm output	1
Operation Mode	Record,Playback,Preview,Backup
Network Protocol	10/100Base-T TCP/IP,UDP,HTTP,NTP,DHCP,DDNS
Network Function	IE remote monitor\Remote control\Remote setup\Remote playback
Backup Device	HDD/USB
Communication Protocol	1x RS-485
Power Supply	Power adapter input AC100~240VAC output DC12V3A15A
Power Consumption	20~42W
Operating Environment	10-90% OH, -10°C ~ 55°C (14°F ~ 131°F)