

Standalone DVR



Features

- H.264 Compression
- D1 Resolution
- 8/16CH Video Input
- Support 1*VGA Output
- 4CH Audio In / 1CH Audio Out
- 8/16 Alarm In / 1 Alarm Out
- Support IE Remote monitor\control\setup\playback
- Support Protocol : TCP/IP,UDP,HTTP,NTP,DHCP,DDNS
- Support 1*RS485 Port for PTZ Function
- Support 4*SATA HDD
- Power adapter input AC100~240VAC output DC12V3A\5A

ADR-2208 / ADR-2216

Specification

Model	ADR-2208	ADR-2216
Video		
Compression	H.264	
Video Input	8CH, BNC (1.0Vp-p,75ohm)	16CH, BNC (1.0Vp-p,75ohm)
Video Output	1*BNC (1.0Vp-p,75ohm), 1*VGA(800*600, 1024*768)	
Looping Output	---	
Audio		
Audio Input	4 (D-SUB , Line-In)	
Audio Output	1*RCA, Line-In (Linear electric level,Resistance:600Ω)	
Recording		
Record Resolution	PAL:720*576 100PPS, NTSC:720*480 120PPS	
Record Speed	PAL:200FPS, NTSC:240FPS	
Record Mode	Continual\Schedule\Motion	
Display Resolution	PAL:720*576 NTSC:720*480	
HDD Interface	4*SATA HDD	
Other		
Alarm Input	8	16
Alarm output	1	
Operation Mode	Record,Playback,Preview,Backup	
Network Protocol	10/100Base-T TCP/IP,UDP,HTTP,NTP,DHCP,DDNS	
Network Function	IE remote monitor\Remote control\Remote setup\Remote playback	
Backup Device	HDD/USB	
Communication Protocol	1*RS-485	
Power Supply	Power adapter input AC100~240VAC output DC12V3A\5A	
Power Consumption	20~42W	
Operating Environment	10-90% OH, -10°C ~ 55°C (14°F ~ 131°F)	