

# Standalone DVR



## Features

- H.264 Compression
- CIF Resolution
- 4CH Video Input
- Support VGA Output
- 4CH Audio In / 1CH Audio Out
- 4 Alarm In / 2 Alarm Out
- Support IE Remote monitor\control\setup\playback
- Support Protocol : TCP/IP,UDP,HTTP,NTP,DHCP,DDNS
- Support 1\*RS485 Port for PTZ Function
- Support 1\*SATA HDD
- Power adapter input AC100~240VAC output DC12V3A\5A

## ADR-3004

### Specification

<b>Model</b>	<b>ADR-3004</b>
<b>Video</b>	
<b>Compression</b>	H.264
<b>Video Input</b>	4CH: BNCx4 input(1.0Vp-p,75ohm)
<b>Video Output</b>	1*BNC (1.0Vp-p,75ohm), 1*VGA(800*600, 1024*768)
<b>Looping Output</b>	---
<b>Audio</b>	
<b>Audio Input</b>	4 (D-SUB , Line-In)
<b>Audio Output</b>	1*RCA, Line-In (Linear electric level,Resistance:600Ω)
<b>Recording</b>	
<b>Record Resolution</b>	PAL:352*288,NTSC: 320*240
<b>Record Speed</b>	PAL:CIF=100fps NTSC:CIF=120fps
<b>Record Mode</b>	Continual\Schedule\Motion
<b>Display Resolution</b>	PAL:720*576 NTSC:720*480
<b>HDD Interface</b>	1*SATA HDD
<b>Other</b>	
<b>Alarm Input</b>	4
<b>Alarm output</b>	2
<b>Operation Mode</b>	Record,Playback,Preview,Backup
<b>Network Protocol</b>	10/100Base-T TCP/IP,UDP,HTTP,NTP,DHCP,DDNS
<b>Network Function</b>	IE remote monitor\Remote control\Remote setup\Remote playback
<b>Backup Device</b>	HDD/USB
<b>Communication Protocol</b>	1x RS-485
<b>Power Supply</b>	Power adapter input AC100~240VAC output DC12V3A\5A
<b>Power Consumption</b>	20~42W
<b>Operating Environment</b>	10-90% OH, -10°C ~ 55°C (14°F ~ 131°F)