

Standalone DVR



Features

- H.264 Compression
- D1 Resolution
- 4/8CH Video Input
- 4CH Audio In / 1CH Audio Out
- 4/8 Alarm In / 1 Alarm Out
- Support IE Remote monitor/control/setup/playback
- Support Protocol : TCP/IP,UDP,HTTP,NTP,DHCP,DDNS
- Support 1*RS485 Port for PTZ Function
- Support USB Mouse
- Support 1*SATA HDD
- Power adapter input AC100~240VA OutputDC19V 4.16A

ADR-3104 / ADR-3108

Specification

Model	ADR-3104	ADR-3108
Video		
Compression	H.264	
Video Input	8CH, BNC (1.0Vp-p,75ohm)	16CH, BNC (1.0Vp-p,75ohm)
Video Output	1*BNC (1.0Vp-p,75ohm)	2*BNC (1.0Vp-p,75ohm)
Looping Output	---	
Audio		
Audio Input	4CH (D-SUB , Line-In)	8CH (D-SUB , Line-In)
Audio Output	1*RCA, Line-In (Linear electric level,Resistance:600Ω)	
Recording		
Record Resolution	PAL:720*576 50PPS; 720*288 100PPS; 360*288 200PPS	
	NTSC:720*480 60PPS; 720*240 120PPS; 360*240 240PPS	
Record Speed	PAL:1/16~25fps/second,NTSC:1/16~30fps/second	
Record Mode	Continual\Schedule\Motion\Alarm	
Display Resolution	PAL:704*576 NTSC:704*480	
HDD Interface	1*SATA HDD	
USB Interface	2*USB (one for USB disk, one for USB mouse)	
Other		
Alarm Input	4	8
Alarm output	1	
Operation Mode	Record,Playback,Preview,Backup	
Network Protocol	10/100Base-T TCP/IP,UDP,HTTP,NTP,DHCP,DDNS	
Network Function	IE remote monitor\Remote control\Remote setup\Remote playback	
Backup Device	HDD/USB	
Communication Protocol	1*RS-485	
Power Supply	Power adapter input AC100~240VA OutputDC19V 4.16A	
Power Consumption	20~42W	
Operating Environment	10-90% OH, -10°C ~ 55°C (14°F ~ 131°F)	