

Bullet Cameras



Model	SKC-41K232	SKC-41KW32	SKC-41F232D	SKC-41F432D	SKC-41C131	SKC-41C132	SKC-41C133	SKC-41C231	SKC-41C232	SKC-41C233	SKC-41C337	SKC-41C338	SKC-41C339
Image Sensor	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/4" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/4" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/4" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD
DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP	Sony DSP
Effective pixels	NTSC: 512 x 492 PAL: 512 x 582	NTSC: 512 x 492 PAL: 512 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582	NTSC: 511 x 492 PAL: 500 x 582
Signal System	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC
Horizontal Resolution	420TVL	420TVL	420TVL	420TVL	420TVL	420TVL	480TVL	420TVL	420TVL	480TVL	420TVL	420TVL	480TVL
Lens	3.7mm Pinhole Lens	3.6mm lens	3.6mm lens	3.6mm lens	3.7mm Pinhole Lens	3.7mm Pinhole Lens	3.7mm Pinhole Lens	3.6mm lens	3.6mm lens	3.6mm lens	3.6mm lens	3.6mm lens	3.6mm lens
Sync. System	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal
Minimum Illumination	0.5Lux@F1.2	0.8Lux@F1.2	0.5Lux@F1.2	0.5Lux@F1.2	1.0Lux@F1.2	0.5Lux@F1.2	0.8Lux@F1.2	1.0Lux@F1.2	0.5Lux@F1.2	0.8Lux@F1.2	1.0Lux@F1.2	0.5Lux@F1.2	0.8Lux@F1.2
S/N Ratio	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB
Shutter Speed	1/50-1/120,000S	1/50-1/120,000S	1/50(60) ~1/100,000	1/50(60) ~1/100,000	1/50(60) ~1/100,000	1/50(60) ~1/100,000	1/50(60) ~1/100,000	1/50(60) ~1/100,000	1/50(60) ~1/100,000	1/50(60) ~1/100,000	1/50(60) ~1/100,000	1/50(60) ~1/100,000	1/50(60) ~1/100,000
White Balance	-	AWB	Auto	Auto	ATW	ATW	ATW	ATW	ATW	ATW	ATW	ATW	ATW
Gain Control	-	Auto	Auto	Auto	on/off	on/off	on/off	on/off	on/off	on/off	on/off	on/off	on/off
Backlight Compensation	Auto	Auto	Auto	Auto	on/off	on/off	on/off	on/off	on/off	on/off	on/off	on/off	on/off
Power Sourcing	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V
Current Consumption	110mA	110mA	110mA	110mA	120mA	120mA	120mA	120mA	120mA	120mA	120mA	120mA	120mA
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)
Dimension (mm)	24(dia)*65(L)	31(dia)*105(L)	27.5(dia)*96(L)	28.6(dia)*89(L)	24(dia)*62(L)	24(dia)*62(L)	24(dia)*62(L)	24(dia)*90(L)	24(dia)*90(L)	24(dia)*90(L)	38(dia)*105(L)	38(dia)*105(L)	38(dia)*105(L)