

Control Keyboards for PTZ Domes



Model	SPK-F101	SPK-F102	SPK-F106	SPK-F107	SPK-J102	SPK-J103	SPK-J212	SPK-J213	SPK-D202	SPK-D203	SPK-D263
Control Type	PTZ Speed Dome	PTZ Speed Dome	PTZ Speed Dome, decoder, Multiplex etc. (3-axis joystick)	PTZ Speed Dome, decoder, Multiplex etc. (3-axis joystick)	PTZ Speed Dome, DVR	PTZ Speed Dome, DVR	PTZ Speed Dome, DVR & Quad (2-axis joystick)	PTZ Speed Dome, DVR & Quad (3-axis joystick)	PTZ Speed Dome (2-axis joystick)	PTZ Speed Dome (3-axis joystick)	PTZ Speed Dome, DVR & Matrix
Function Display	LCD On-Screen Display	-	LCD On-Screen Display (5-inch color LCD screen)	LCD On-Screen Display	LCD On-Screen Display	LCD On-Screen Display	LCD On-Screen Display	LCD On-Screen Display	LCD On-Screen Display	LCD On-Screen Display	LCD On-Screen Display
Output Control	control up to 32pcs high speed dome	control up to 32pcs high speed dome	control up to 32pcs high speed dome	control up to 32pcs high speed dome	control up to 128 pcs high speed dome	control up to 512 pcs high speed dome	control up to 64pcs high speed dome	control up to 64pcs high speed dome	control up to 32pcs high speed dome	control up to 32pcs high speed dome	control up to 32pcs high speed dome
Baud Rate	2400, 4800, 9600 bps	2400, 4800, 9600, 19200 bps	2400, 4800, 9600, 19200 bps	2400, 4800, 9600, 19200 bps	2400, 4800, 9600, 19200 bps	2400, 4800, 9600, 19200 bps	2400, 4800, 9600 bps	2400, 4800, 9600 bps	2400, 4800, 9600, 19200 bps	2400, 4800, 9600, 19200 bps	2400, 4800, 9600 bps
Communication Port	RS485	RS485 / RS232	RS485 / RS232	RS485 / RS232	RS485	RS485	RS485	RS485	RS485 / RS232	RS485 / RS232	RS485, RS422, RS232, RJ45
Communication Distance	1200M	1200M (RS485)	1200M	1200M	1500M (0.5MM twisted-pair)	1500M (0.5MM twisted-pair)	Up to 1.2 KM	Up to 1.2 KM	Up to 1.2 KM	Up to 1.2 KM	1.2km (RS485 and Rs422 can achieve it)
Rated power	N/A	N/A	N/A	N/A	N/A	N/A	< 3W	< 3W	N/A	N/A	2.5W
Power Supply	DC12V	9V-12V AC/DC	DC12V/2.0A	DC12V/2.0A	DC9V 500mA	DC9V 500mA	DC9V ±10%	DC9V ±10%	9V-12V AC/DC	9V-12V AC/DC	9V-12VAC/DC
Operating Temperature	0°C~50°C	0°C~50°C	0°C~50°C	0°C~50°C	-10°C ~ 60°C	-10°C ~ 60°C	-10°C~50°C	-10°C~50°C	0°C~50°C	0°C~50°C	0°C~40°C
Dimension	315×130×57(mm)	189mm (W) x60mm (H) x 130mm (D)	390×165×80 (mm)	390×165×80 (mm)	202(L)× 168(W)× 48(H)mm	330(L) x 176.6(W) x 112.5(H)mm	314mm (W) x209mm (H)	314mm (W) x 209mm (H)	218mm (W) x180mm (H) x 55mm (D)	218mm (W) x180mm (H) x 55mm (D)	375mm (L) x165mm (W) x 95mm (H)