

H.264 Real-time Standalone DVR



Features

- 2 channel at D1 synchronously playback
- Support H.264/MJPEG 2 types coding compression
- Support mouse , 4 USB2.0 ports and SATA HDD
- Add key shortcut such as Playback, Copy and PTZ operation, which make interface even friendly and convenience.
- Optional CBR or VBR mode
- Adjustable frame rate, which helps with better frame rate utilization according to your practical system use.
- Support video loop out; Support Dial-Up function.
- Multi-level user management, support user name input.
- Simplified Terminal software(netclient), connect to more than 100sets of DVR at the same time.

DMF-7204

Specification

Model	DMF-7204
Video	
Compression	H.264/MJPEG
Video input	4CH BNC input(1.0Vp-p,75ohm)
Video output	2CH BNC out (1.0Vp-p,75ohm), 1 VGA output(800*600, 1024*768, 1280*1024)
Video looping output	4CH BNC input(1.0Vp-p,75ohm)
Audio	
Compression	G.711/ADPCM
Audio input	4CH BNC output
Audio output	1CH RCA out
Record/Play	
Record resolution	D1 704×576(PAL), 704×480(NTSC)
Record quality	5 in all, from high to low
Record Speed	Real-time 25(PAL)/30(NTSC)fps per Channel
Play resolution	D1 704×576(PAL), 704×480(NTSC)
Play back	Support 2CH play back simultaneously with D1 Res.
Basic storage	Support 4 SATA HDD (Max. 2TB/HDD)
Alarm	
Input	4CH NO/NC programmable
Output	4CH NO/NC
Other	
Working Mode	Multiplex(Record, Playback, Netview, Netplayback, Liveview)
Network	RJ45, 10/100Mbase T Ethernet
Backup device	Removable HDD/USB DVD, CD Writer/Network/
Communication protocol	RS-232, 2x RS-485/422, 3x USB2.0 port plus built-in 1 USB2.0 port
Power Supply	AC 100-240V 50/60Hz
Weight	11KG
Dimension(WxHxD)	440x100x450 mm 2U
Operating Environment	0-95% OH, -10°C ~ 55°C (14°F ~ 131°F)