

H.264 Real-time Standalone DVR



Features

- 2 channel at D1 synchronously playback
- Support H.264/MJPEG 2 types coding compression
- Support mouse , 4 USB2.0 ports and SATA HDD
- Add key shortcut such as Playback, Copy and PTZ operation, which make interface even friendly and convenience.
- Optional CBR or VBR mode
- Adjustable frame rate, which helps with better frame rate utilization according to your practical system use.
- Support video loop out; Support Dial-Up function.
- Multi-level user management, support user name input.
- Simplified Terminal software(netclient), connect to more than 100sets of DVR at the same time

DMF-7208 / DMF-7212

Specification

Model	DMF-7208	DMF-7212
Video		
Compression	H.264/MJPEG	
Video input	8CH BNC input (1.0Vp-p,75ohm)	12CH BNC input(1.0Vp-p,75ohm)
Video output	2CH BNC out (1.0Vp-p,75ohm), 1 VGA output(800*600, 1024*768, 1280*1024)	
Video looping output	8CH BNC input(1.0Vp-p,75ohm)	12CH BNC input(1.0Vp-p,75ohm)
Audio		
Compression	G.711/ADPCM	
Audio input	8CH BNC output	12CH BNC output
Audio output	1CH RCA out	
Record/Play		
Record resolution	D1: 704*576(PAL) 704*480(NTSC)	
Record quality	5 Levels	
Record Speed	Real-time 25(PAL)/30(NTSC)fps per Channel	
Play resolution	D1: 704*576(PAL) 704*480(NTSC)	
Play back	Support 2CH play back simultaneously with D1 Res.	
Basic storage	Support 8 SATA HDD (Max. 2TB/HDD)	
Alarm		
Input	8CH NO/NC programmable	12CH NO/NC programmable
Output	4CH NO/NC	
Other		
Working Mode	Multiplex(Record, Playback, Netview, Netplayback, Liveview)	
Network	RJ45, 10/100Mbase T Ethernet	
Backup device	Removable HDD/USB DVD, CD Writer/Network/	
Communication protocol	RS-232, 2x RS-485/422, 3x USB2.0 port plus built-in 1 USB2.0 port	
Power Supply	AC 100-240V 50/60Hz	
Weight	11KG	
Dimension(WxHxD)	440x100x450 mm 2U	
Operating Environment	0-95% OH, -10°C ~ 55°C (14°F ~ 131°F)	

* DMF-7212M: with Matrix Output Feature