

H.264 Real-time Standalone DVR



Features

- 24-bit color menu icon: that creates crystal clear image effect.
- Add key shortcut such as Playback, Copy and PTZ operation, which make interface even friendly and convenience.
- Optional CBR or VBR mode
- Adjustable frame rate, which helps with better frame rate utilization according to your practical system use.
- 4-channel synchronously playback
- Support mouse and 4 USB2.0 ports
- Support video loop out; Support Dial-Up function.
- Multi-level user management, support user name input.
- Simplified Terminal software(netclient), connect to more than 100sets of DVR at the same time

DMS-9010S / DMS-9016S

Specification

Model	DMS-9010S	DMS-9016S
Video		
Compression	H.264	
Video input	10CH BNC input (1.0VP-P,75ohm)	16CH BNC input (1.0VP-P,75ohm)
Video output	1CH BNC output (1.0VP-P,75ohm)	
	1 VGA output (800*600, 1024*768, 1280*1024)	
Video looping outputs	10CH BNC input (1.0VP-P,75ohm)	16CH BNC input (1.0VP-P,75ohm)
Recording / Play Function		
Record resolution	CIF: 352*288(PAL) 352*240(NTSC),	
Recording Speed	Real-time 25(PAL)/30(NTSC)fps per Channel	
Record quality	5 Levels	
Display	1/4/6/9/16	
HDD	Support 8 SATA HDD (Max. 2TB/HDD)	
Paly back	4 channel simultaneously playback	
Other Function		
PTZ Camera	RS-485/422 support	
Network	RJ-45 , support PPPoE	
Audio input	---	
Audio output	---	
Alarm	10-ch Input/4-ch Output	16-ch Input/4-ch Output
Mouse	USB Mouse	
Communication Protocol	RS-232, 2x RS-485/422, 3x USB2.0 port plus built-in 1 USB2.0 port	
Mechanical		
Working temperature	-10°C ~ 55°C (14°F ~ 131°F)	
Working humidity	10%~95%	
Power supply	AC 110~240V 50/60Hz	
Dimension(W*H*D)	450mm*100mm*440mm 2U	
Weight	11KG	

* DMS-9016SM: With Matrix Output Feature.