

Indoor PTZ Speed Domes



Features

- Celerity installation structure, support hot plugging.
- Built-in 216 times zoom.
- Pan resolution: 480line; 0.9Lux
- Screen display the position of the pan/tilt, the temperature of the dome, humanity focal length/speed matching technique.
- At 128 presets (title settable), pan 360 degree rotation
- seriously, tilt 90 degree rotation, auto-overturn, manual speed: 0.4~320 degree/s.
- 8 display ears can be set title, 4 Pattern lines, support the ordered speed between left and right limit.
- No less than 180s record, 4 scan lines, support the ordered speed between left and right limit.
- Auto-scan (still support operation of zoom, tilt)
- Timely auto-active function, can transfer the preset or startup auto-cruise, pattern, scan and display area.

Support Motion Tracking Function (optional)

DSP-D81E26 / DSP-D81E30 / DSP-D81E35W / DSP-D81E36W

Specification

Model	DSP-D81E26	DSP-D81E30	DSP-D81E35W	DSP-D81E36W
Camera	Sony EX-980 Day/Night Color 26x Zoom Camera	Hitachi Day/Night Color 30x Zoom Camera	Hitachi Day/Night WDR Color 35x Zoom Camera	Sony EX-1010 Day/Night WDR Color 36x Zoom Camera
Sync. System	Internal/External (V-Lock)	Internal/Line-Lock	Internal/Line-Lock	Internal/External (V-Lock)
Scanning Mode	2:1 Interlacing			
Definition	520TVL	520TVL	480TVL	530TVL
Minimum Illumination	Color:1.0Lux B/W: 0.001Lux	Color:0.7Lux B/W: 0.01Lux	Color:0.7Lux B/W: 0.01Lux	Color:0.7Lux B/W: 0.01Lux
Focus Length	26x Zoom Lens (3.5~91.0mm)	30x Zoom Lens (3.4~108mm)	35x Zoom Lens (3.4~119.0mm)	36x Zoom Lens (3.4~122.4mm)
Digital Zoom	12x	12x	12x	12x
WDR	---	---	Yes	Yes
Backlight Compensation	On/Off			
White balance	Auto, ATW, Indoor, Outdoor, One-push, Manual	Auto/manual	Auto/manual	Auto, ATW, Indoor, Outdoor, One-push, Manual
AGC	Auto/Manual			
S/N Ratio	≥50dB			
Video Signal Output	1.0±0.2Vp_p			
Communication Mode	RS485, Manchester code, BI-BPASE code, as coaxial control			
Communication Baudrate	2400/4800/9600/19200 bps			
Display zone	8 programmable zones with titles(support auto-scan within zones)			
Address setting	1~254			
Rotation Speed	Pan 0.4~320°/S ; Tilt 0.4~150°/S			
Pan/Tilt Rotation	Pan360°continuously; tilt 0-90°with auto-flip			
Preset	128 presets, can be labeled with editable titles			
Operation environment	-10°C ~ 50°C (14°F ~ 122°F)			
Environmental Humidity	0~95% no compensation			
Power Supply	AC24V±4V			
Consumption	10w			
Weight	N.W. 2.9Kg G.W. 4.8Kg			

Dimension

