

Indoor Mini PTZ Domes

JCC-DN2110D (DSP-81N10)



Features

- Samsung 1/4" D/N High Res. Color 10x Camera
- Auto brightness controlling
- Auto white balance
- Auto back-light compensation
- Auto aperture
- Auto focus
- High sensitivity, high resolution, and integrated digital processing
- Built-in decoder Integrated and multi-protocol include PELCO-D PELCO-P FACTORY and main-stream protocols
- Support pan 360 continuously and tilt 0-90 , and may rotate180- with auto flip
- Video OSD menu
- DC 12V

JCC-DN2110D (DSP-81N10)

Specification

Model	JCC-DN2110D (DSP-81N10)
Imaging Element	1/4" CCD
Camera	Samsung 1/4" D/N High Res. Color 10x Camera
Scanning System	625lines, 50field/s
White Balance	Auto/manual
Gain Control	Auto Gain Control
S/N	≥50dB
Illumination	Color : 0.5Lux or B/W : 0.07 Lux
Shutter	1/50-1/120,000 S
Lens	10 times optical magnified lens
Magnification	100times(10 times optical×10 times digital)
Video Output	MultipleVideoOutput, 1.0Vp-p
Environmental Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Environmental Humidity	0~95%(no condensation)
Baud rate(RS485)	2400/4800/9600/19200bps
Communication Protocol	Pelco-D / Pelco-P
Pan rotation	360° continuously
Tilt rotation	Tilt90° with auto-flip
Rotation speed	Pan0.5°~160°/S, Tilt0.5°~90°/S
Preset	128
Monitor way	Preset/tour/scan/pattern
Speed	Limitless variable-speedcontrolling
Power supply	DC 12V/1.5A
Cosumption	<9W
Weight	N: 2.5kg G: 3.0kg

Dimension

