

H.264 Real-time Standalone DVR



Work with iPhone, blackberries and windows smart phones

Features

- Support H.264/JPEG 2 types coding compression
- Support mouse, 1x USB2.0 ports and 1x SATA HDD
- Support multi mode, surveillance, playback, view simultaneously on the same screen
- Support PPPoE, DHCP etc.
- 4CH playback simultaneously
- Support E-mail Function
- Remote view by IE Browser
- Support cell phone surveillance
- DC12V/3A

DVR-4D04 / DVR-4D08

Specification

Model	DVR-4D04	DVR-4D08
Video		
Compression	H.264(main profile)/JPEG	
Video input	4CH BNC input (1.0Vp-p,75ohm)	8CH BNC input(1.0Vp-p,75ohm)
Video output	1CH BNC out (1.0Vp-p,75ohm), 1 VGA (800*600, 1024*768, 1280*1024)	
Audio		
Compression	ADPCM	
Input	4CH BNC input	4CH BNC input
Output	1CH Mini jack(linear voltage,1KΩ), support drive earphone directly	
Record/Play		
Record resolution	D1 704*576(PAL), 704*480(NTSC) CIF 352*288(PAL), 352*240(NTSC)	CIF 352*288(PAL), 352*240(NTSC)
Record quality	5 Levels	
Record Speed	25(PAL)/30(NTSC)FPS all real time flexible, support non-realtime D1	
Play resolution	D1 704*576(PAL), 704*480(NTSC)	
Play back	4CH playback simultaneous	4CH at CIF simultaneous play back
Basic storage	Support 1x SATA HDD (Max. 2TB/HDD)	
Alarm		
Input	4CH	
Output	1CH	
Other		
System Resource	Multi-CH recording, Playback, Netview, Netplayback, Liveview)	
Network	RJ45, 10/100Mbase-T Ethernet, support PPPoE, DDNS, DHCP	
Backup device	1 USB 2.0, support flash memory, Remote HDD	
Communication protocol	1x RS-232, 1x RS-485, 1x USB1.1 port for mouse, 1x USB2.0 port	
Power Supply	DC12V/3A	
Power(w/o HDD)	<10W	
Weight	2.3KG	
Dimension(WxHxD)	250*260*50mm	
Operating Environment	10-95% OH, -10°C ~ 55°C (14°F ~ 131°F)	