

H.264 Real-time Standalone DVR



Features

- Support H.264/MJPEG 2 types coding compression
- Support mouse , 1x USB2.0 ports and 4x SATA HDD
- Support multi mode, surveillance, playback, view simultaneously on the same screen
- Support PPPoE, DHCP etc.
- Support E-mail Function
- 2Ch Video Output
- Remote view by IE Browser
- AC220/230V 50/60Hz

DVR-4T04 / DVR-4T08 / DVR-4T16

Specification

Model	DVR-4T04	DVR-4T08	DVR-4T16
Video			
Compression	H.264/MJPEG		
Video input	4CH BNC input	8CH BNC input	16CH BNC input
Video output	2CH BNC out (1.0Vp-p,75ohm), 1 VGA output(800*600, 1024*768, 1280*1024)		
Audio			
Compression	ADPCM		
Audio input	4CH BNC input	8CH BNC input	16CH BNC input
Audio output	1CH RCA out		
Record/Play			
Record resolution	CIF 352*288(PAL), 352*240(NTSC)		
Record quality	5 Levels		
Record Speed	Real-time 25(PAL)/30(NTSC)fps per Channel		
Play resolution	D1 704*576(PAL), 704*480(NTSC)		
Play back	1CH at CIF Res.		
Basic storage	Support 4x SATA HDD (Max. 2TB/HDD)		
Alarm			
Input	4CH	8CH	16CH
Output	2CH	4CH	8CH
Other			
Working Mode	Multiplex(Record, Playback, Netview, Netplayback, Liveview)		
Network	RJ45, 10/100Mbase-T Ethernet, TCP/IP, UDP, Multicast, PPPoE, DHCP		
Backup device	Removable HDD/USB DVD, Network		
Communication protocol	1x RS-232, 1x RS-485, 1x USB1.1 port, 1x USB2.0 port		
Power Supply	AC220/230V 50/60Hz		
Weight	11KG		
Dimension(WxHxD)	450×100×440 mm 2U		
Operating Environment	10-95% OH, -10°C ~ 55°C (14°F ~ 131°F)		