

# Penatplex Stand-Alone DVR



Model	SS-HDR-8804	SS-HDR-8808	SS-HDR-8816	SS-HDR-8604	SS-HDR-8608	SS-HDR-8616
Compression	H.264	H.264	H.264	H.264	H.264	H.264
Video Input	4CH, BNC (1.0Vp-p,75ohm)	8CH, BNC (1.0Vp-p,75ohm)	16CH, BNC (1.0Vp-p,75ohm)	4CH, BNC (1.0Vp-p,75ohm)	8CH, BNC (1.0Vp-p,75ohm)	16CH, BNC (1.0Vp-p,75ohm)
Video Output	BNC*1 (1.0Vp-p,75ohm), VGA Out	BNC*1 (1.0Vp-p,75ohm), VGA Out	BNC*1 (1.0Vp-p,75ohm), VGA Out	BNC*1 (1.0Vp-p,75ohm), VGA Out	BNC*1 (1.0Vp-p,75ohm), VGA Out	BNC*1 (1.0Vp-p,75ohm), VGA Out
Looping Output	-	-	-	-	-	-
Audio Input	8k 8bit, 4CH	8k 8bit, 4CH	8k 8bit, 4CH	8k 8bit, 4CH	8k 8bit, 4CH	8k 8bit, 4CH
Audio Output	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH
Record Resolution	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576, 352X288 ; NTSC:720X480, 352X240
Record Speed	PAL:CIF=200fps, D1=50fps NTSC:CIF=240fps, D1=60fps	PAL:CIF=200fps, D1=50fps NTSC:CIF=240fps, D1=60fps	PAL:CIF=400fps NTSC:CIF=480fps	PAL:CIF=200fps, D1=50fps NTSC:CIF=240fps, D1=60fps	PAL:CIF=200fps, D1=50fps NTSC:CIF=240fps, D1=60fps	PAL:CIF=400fps NTSC:CIF=480fps
Record Mode	Manual/Sensor/Timer Motion Detection	Manual/Sensor/Timer Motion Detection	Manual/Sensor/Timer Motion Detection	Manual/Sensor/Timer Motion Detection	Manual/Sensor/Timer Motion Detection	Manual/Sensor/Timer Motion Detection
Display Resolution	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480
HDD	Support 2*HDD	Support 2*HDD	Support 2*HDD	Support 2*HDD	Support 2*HDD	Support 2*HDD
Network Port	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45
Backup Device	HDD/USB/ DVD-RW(Optional)	HDD/USB/ DVD-RW(Optional)	HDD/USB/ DVD-RW(Optional)	HDD/USB	HDD/USB	HDD/USB/ DVD-RW(Optional)
Alarm Input	4 CH(Optional)	4 CH(Optional)	4 CH(Optional)	4 CH(Optional)	4 CH(Optional)	4 CH(Optional)
Alarm Output	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM
Power Supply	220V/110V	220V/110V	220V/110V	12V/4A	12V/4A	12V/5A
Power Consumption	6W(w/o HDD)	6W(w/o HDD)	9W(w/o HDD)	6W(w/o HDD)	6W(w/o HDD)	9W(w/o HDD)
Remote Controller	Yes	Yes	Yes	Yes	Yes	Yes

# Penatplex Stand-Alone DVR



Model	SS-HDR-8704	SS-HDR-8708	SS-HDR-8204	SS-HDR-8208	SS-HDR-8216	SS-HDR-8904	SS-HDR-8908	SS-HDR-8916
Compression	H.264	H.264	H.264	H.264	H.264	H.264	H.264	H.264
Video Input	4CH, BNC (1.0Vp-p,75ohm)	8CH, BNC (1.0Vp-p,75ohm)	4CH, BNC (1.0Vp-p,75ohm)	8CH, BNC (1.0Vp-p,75ohm)	16CH, BNC (1.0Vp-p,75ohm)	4CH, BNC (1.0Vp-p,75ohm)	8CH, BNC (1.0Vp-p,75ohm)	16CH, BNC (1.0Vp-p,75ohm)
Video Output	BNC*1 (1.0Vp-p,75ohm), VGA Out	BNC*1 (1.0Vp-p,75ohm), VGA Out	BNC*1 (1.0Vp-p,75ohm), VGA Out	BNC*1 (1.0Vp-p,75ohm), VGA Out / HDMI	BNC*1 (1.0Vp-p,75ohm), VGA Out / HDMI	BNC*1 (1.0Vp-p,75ohm), VGA Out / HDMI	BNC*1 (1.0Vp-p,75ohm), VGA Out	BNC*1 (1.0Vp-p,75ohm), VGA Out
Looping Output	-	-	-	-	-	-	-	-
Audio Input	8k 8bit, 4CH	8k 8bit, 8CH	8k 8bit, 4CH	8k 8bit, 8CH	8k 8bit, 16CH	8k 8bit, 4CH	8k 8bit, 4CH	8k 8bit, 4CH
Audio Output	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH	8k 8bit, 1CH
Record Resolution	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576 NTSC:720X480	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576 NTSC:720X480	PAL:720X576, 352X288 ; NTSC:720X480, 352X240	PAL:720X576, 352X288 ; NTSC:720X480, 352X240
Record Speed	CIF=Realtime D1=Realtime	CIF=8CH Realtime D1=6fps/ch	D1: 4CH Realtime	CIF:8CH Realtime D1:8CH Realtime	CIF: 16CH Realtime D1=6fps/ch	D1: 4CH Realtime	CIF:8CH Realtime D1:8CH Realtime	CIF: 16CH Realtime D1=6fps/ch
Record Mode	Sensor/Timer Motion Detection	Sensor/Timer Motion Detection	Sensor/Timer Motion Detection	Sensor/Timer Motion Detection	Sensor/Timer Motion Detection	Sensor/Timer Motion Detection	Sensor/Timer Motion Detection	Sensor/Timer Motion Detection
Display Resolution	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480	PAL:720*576 NTSC:720*480
HDD	Support 2*HDD	Support 2*HDD	Support 2*HDD	Support 2*HDD	Support 2*HDD	Support 8*HDD	Support 8*HDD	Support 8*HDD
Network Port	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45
Backup Device	HDD/USB	HDD/USB	HDD/USB DVD-RW(Optional)	HDD/USB DVD-RW(Optional)	HDD/USB DVD-RW(Optional)	HDD/USB DVD-RW(Optional)	HDD/USB DVD-RW(Optional)	HDD/USB DVD-RW(Optional)
Alarm Input	4 CH	8CH	4 CH	8 CH	16 CH	4 CH	8 CH	16 CH
Alarm Output	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM	Relay Output, NO, NC, COM
Power Supply	12V/5A	12V/5A	12V/5A	12V/5A	12V/5A	220V/110V	220V/110V	220V/110V
Power Consumption	10W(w/o HDD)	10W(w/o HDD)	12W(w/o HDD)	12W(w/o HDD)	12W(w/o HDD)	12W(w/o HDD)	12W(w/o HDD)	12W(w/o HDD)
Remote Controller	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes