

H.264 Standalone DVR



Features

- H.264 compression
- CIF Recording Resolution
- 4 Video input / 1 Video output
- 4 Alarm input / 2 Alarm output
- Support TCP/IP protocols (support ARP, RARP, IP, TCP, PPPOE, DHCP, etc.)
- Support PPPOE
- Complete controlling functions from remote client or IE browse to set up parameter through network
- Update through network and achieve through network to help user maintenance
- Support the local monitor and local VGA, support TV wall function
- Provide SDK package for client managing device

HDR-7004A

Specification

Model	HDR-7004A
Video	
Video input	4-channel composite video input
Video output	1 BNC video out
	1 VGA output
Recording / Play Function	
Compression Format	Video:H.264
Record quality	6 levels optional
Total Frames	PAL:100fps ; NTSC:120fps
Recording resolution	CIF(PAL:352*288 / NTSC:352*240)
Preview resolution	BNC: 704*576 (PAL) / 704*480 (NTSC) VGA: 800*600, 1024*768, 1280*768, 1360*768 adjustable
Other Function	
Other	Watchdog / Dual stream / PPPoE / DHCP / DDNS
Alarm input	4 alarm inputs
Alarm output	2 alarm outputs
Audio input	4-channel input
Audio output	1 BNC output
Mechanical	
HDD	1 SATA interface
Network port	RJ45 10M/100M Ethernet Interface
Backup	USB2.0 / Remote Backup
I/O Interface	RS-485 for PTZ ; PS2 for Mouse
Working temperature	-10°C ~ 55°C (14°F ~ 131°F)
Working humidity	10%~90%
Power supply	AC 220+- 30% V, 50+- 3% HZ or 110+- 20% V, 60+- 3% HZ
Power consumption	20W (without hard disk)
Dimension	325mm*200mm*55mm
Weight	4.5 kg (w/o HD)