

# H.264 Standalone DVR



## Features

- H.264 compression
- CIF Recording Resolution
- 8/16ch Video inputs / 1 Video output, VGA output
- 8/16 Alarm inputs / 2 Alarm output
- Support TCP/IP protocols (support ARP, RARP, IP, TCP, PP-POE, DHCP, etc.)
- Support PPPOE
- Complete controlling functions from remote client or IE browse to set up parameter through network
- Update through network and achieve through network to help user maintenance
- Support the local monitor and local VGA, support TV wall function
- Provide SDK package for client managing device

## HDR-7008 / HDR-7008A / HDR-7016 / HDR-7016A

### Specification

Model	HDR-7008	HDR-7008A	HDR-7016	HDR-7016A
<b>Video</b>				
Video input	8ch composite video input		16ch composite video input	
Video output	1 BNC video out			
	1 VGA output			
<b>Recording / Play Function</b>				
Compression Format	Video:H.264			
Record quality	6 levels optional			
Total Frames	PAL: 200 fps / NTSC: 240 fps		PAL: 400 fps / NTSC: 480 fps	
Recording resolution	CIF(PAL:352*288 / NTSC:352*240)			
Preview resolution	BNC: 704*576 (PAL) / 704*480 (NTSC) VGA: 800*600, 1024*768, 1280*768, 1360*768 adjustable			
<b>Other Function</b>				
Other	Watchdog / Dual Stream / PPPoE / DHCP / DDNS / VFD display			
Alarm input	8 alarm inputs		16 alarm inputs	
Alarm output	2 alarm outputs			
Audio input	-	8-ch input	-	16-ch input
Audio output	1 BNC audio output			
<b>Mechanical</b>				
HDD	2 SATA interface			
Network port	RJ45 10M/100M Ethernet Interface			
Backup	USB2.0 / High Speed SATA / Remote Backup			
I/O Interface	RS232/RS485, RS485 for PTZ, PS/2 for Mouse			
Working temperature	-10°C ~ 55°C (14°F ~ 131°F)			
Working humidity	10%~90%			
Power supply	220±30% V, 50±3% Hz or 110±20% V, 60±3% Hz			
Power consumption	25W (without hard disk)		30W (without hard disk)	
Dimension	405mm*310mm*55mm			
Weight	5.5KG ( without hard disk)			