

H.264 Standalone DVR



Features

- H.264 compression
- CIF Recording Resolution
- 4 Video input / 1 Video output
- 4 Alarm input / 4 Alarm output
- Support TCP/IP protocols (support ARP, RARP, IP, TCP, PP-POE, DHCP, etc.)
- Support PPPOE
- Complete controlling functions from remote client or IE browse to set up parameter through network
- Update through network and achieve through network to help user maintenance
- Support the local monitor and local VGA, support TV wall function
- Provide SDK package for client managing device

HDR-8004 / HDR-8004A

Specification

Model	HDR-8004	HDR-8004A
Video		
Video input	4-channel composite video input	
Video output	1 BNC video out ; Loop Video output	
	1 VGA output	
Recording / Play Function		
Compression Algorithm	Video:H.264 ; Audio:G.711	
Record quality	6 levels optional	
Total Frames	PAL:100fps ; NTSC:120fps	
Recording resolution	CIF(PAL:352*288 / NTSC:352*240)	
Preview resolution	BNC:704*576(PAL) / 704*480(NTSC) ; VGA: 800*600/1024*768	
Other Function		
Other	Watchdog / Dual stream / PPPoE / DHCP / DDNS	
Alarm input	4 alarm inputs	
Alarm output	2 alarm outputs	
Audio input	-	4-channel input
Audio output	-	1 BNC output
Mechanical		
HDD	4 SATA interfaces	
Network port	RJ45 10M/100M Ethernet Interface	
Backup	USB2.0 / High Speed SATA / Remote Backup	
I/O Interface	RS-232/RS-485 for PTZ ; PS2 for Mouse	
Working temperature	-10°C ~ 55°C (14°F ~ 131°F)	
Working humidity	10%~90%	
Power supply	AC 220+- 30% V, 50+- 3% HZ or 110+- 20% V, 60+- 3% HZ	
Power consumption	20W(w/o HD)	
Dimension	535mm*535mm*215mm	
Weight	10 kg (w/o HD)	