

H.264 Standalone DVR



Features

- H.264 compression
- D1 Recording Resolution
- 4/8/16 Video input / 1 Video output
- 4/8/16 Alarm input / 4 Alarm output
- Support TCP/IP protocols (support ARP, RARP, IP, TCP, PPPOE, DHCP, etc.)
- Support PPPOE
- Complete controlling functions
- from remote client or IE browse to set up parameter through network
- Update through network and achieve through network to help user maintenance
- Support the local monitor and local VGA, support TV wall function
- Provide SDK package for client managing device
- Built in DVD writer (8CH & 16CH)

HDR-8204 / HDR-8208 / HDR-8216 Series

Specification

Model	HDR-8204	HDR-8208	HDR-8208R	HDR-8216	HDR-8216R
Video					
Video input	4-ch composite video input	8-ch composite video input		16-ch composite video input	
Video output	1 BNC video out				
	1 VGA output				
Recording / Play Function					
Compression Algorithm	Video:H.264 ; Audio:G.711				
Record quality	6 levels optional				
Total Frames	PAL:100fps / NTSC:120fps	PAL:200 fps / NTSC:240 fps		PAL:400 fps / NTSC:480 fps	
Recording resolution	D1: PAL (704*576), NTSC (704*480)				
Preview resolution	BNC:704*576(PAL) / 704*480(NTSC) ; VGA:800*600				
Playback	1ch at the same time				
Other Function					
Other	Watchdog / Dual Stream / PPPoE / DHCP / DDNS				
Alarm input	4 alarm inputs	8 alarm inputs		16 alarm inputs	
Alarm output	4 alarm outputs				
Audio input	4-ch input	8-ch input		16-ch input	
Audio output	1 BNC output				
Mechanical					
HDD	4 SATA	8 SATA interfaces		8 SATA interfaces	
DVD-RW	-	-	Built-in	-	Built-in
Network port	RJ45 10M/100M Ethernet Interface				
Backup	USB2.0 / High Speed SATA / Remote Backup				
I/O Interface	RS232/RS485, RS485 for PTZ ; PS2 for Mouse				
Working temperature	-10°C ~ 55°C (14°F ~ 131°F)				
Working humidity	10%~90%				
Power supply	AC 220+- 30% V, 50+- 3% HZ or 110+- 20% V, 60+- 3% HZ				
Power consumption	20W(w/o HD)	25W(w/o HD)		30W(w/o HD)	
Dimension	440mm*420mm*100mm				
Weight	11 kg (w/o HD)				