

Embedded PTZ Speed Dome

JSP-71H18

JSP-D71H18



Features

- 360° continuous pan, 90° in tilt, 180° in auto flip
- Max 128 presets, programmable
- Low speed by manual is widen range, catch on the target accurately
- Auto pan scan
- Three-dimensional scan between two presets
- Call camera menu
- Focus & Iris speed is adjustable
- Auto/Manual white balance
- Manual/Auto backlight compensation
- Tour through presets in groups
- Tour speed is adjustable
- Proportional controlling Function
- Power up function
- Turn angle display function
- Inner mount preventing from surge or lightning strike
- Install easily
- Auto protection Function is on when power cutting
- AC24V available with additional cost

JSP-71H18 / JSP-D71H18

Specification

Model	JSP-71H18	JSP-D71H18
CCD	1/4" Super HAD CCD	1/4" Exview HAD CCD
Camera	Sony EX-45CP Color 18x Zoom Camera	Sony EX-480 Day/Night Color 18x Zoom Camera
Signal format	PAL/NTSC	
Picture Element	NTSC: 768(H) x 494(V) ; PAL: 752(H) x 582(V)	
Low Sensitivity	0.7Lux	0.002Lux
Focal Length	4.1~73.8mm	4.1~73.8mm
Resolution	480TVL	
Electronic Shutter	1/50~1/10,000s	1/3~1/10,000s
Zoom Ratio	18x	18x
Digital Zoom	12x	12x
Pan speed	0.1°- 240°/S	
Tilt speed	0.1°- 120°/S	
Manual tilt scale	0°- 90°	
Scan scale	360° continuously	
Presets number	Max 128	
S/N ratio	>48dB	
Communication format	RS-485	
Built-in protocol	Pelco P or D protocol is identified automatically	
Applicable temperature	-10°C ~ 50°C (14°F ~ 122°F)	
Baud rate	1200 / 2400 / 4800 / 9600	
Consumed power	≤20W	
Voltage	DC12V	

Dimension

