

Embedded PTZ Speed Dome

JSP-71H23

JSP-D71H30W

JSP-D71H30W



Features

- 360° continuous pan, 90° in tilt, 180° in auto flip
- Max 128 presets, programmable
- Low speed by manual is wider range, catch on the target accurately
- Auto pan scan
- Three-dimensional scan between two presets
- Call camera menu
- Focus & Iris speed is adjustable
- Auto/Manual white balance
- Manual/Auto backlight compensation
- Tour through presets in groups
- Tour speed is adjustable
- Proportional controlling Function
- Power up function
- Turn angle display function
- Inner mount preventing from surge or lightning strike
- Install easily
- Auto protection Function is on when power cutting
- AC24V available with additional cost

JSP-71H23 / JSP-D71H23 / JSP-D71H30W

Specification

Model	JSP-71H23	JSP-D71H23	JSP-D71H30W
CCD	1/4" Super HAD CCD	1/4" Exview HAD CCD	1/4" Exview HAD CCD
Camera	Samsung SDM-230 Color 23x Zoom Camera	Samsung SDM-231 Day/Night Color 23x Zoom Camera	Samsung SDM-330 Day/Night WDR Color 30x Zoom Camera
Signal format	PAL/NTSC		
Picture Element	NTSC: 768(H) x 494(V) ; PAL: 752(H) x 582(V)		
Low Sensitivity	0.7Lux	Color: 0.7Lux B/W:0.007Lux	Color:0.4Lux B/W: 0.0006Lux
Focal Length	3.84~88.4mm	3.84~88.4mm	3.3~99mm
W.D.R.	---	---	O
Resolution	Color:540TVL B/W:570TVL		
Electronic Shutter	1/50~120,000 sec.	1/50~1/10,000 sec.	1/50~1/40,000 sec.
Zoom Ratio	23x	23x	30x
Digital Zoom	10x	10x	8x
Pan speed	0.1°- 240°/S		
Tilt speed	0.1°- 120°/S		
Manual tilt scale	0°- 90°		
Scan scale	360° continuously		
Presets number	Max 128		
S/N ratio	>48dB		
Communication format	RS-485		
Built-in protocol	Pelco P or D protocol is identified automatically		
Applicable temperature	-10°C ~ 50°C (14°F ~ 122°F)		
Baud rate	1200 / 2400 / 4800 / 9600		
Consumed power	≤20W		
Voltage	DC12V		

Dimension

