

# Indoor PTZ Speed Dome

JSP-71M18

JSP-D71M23



## Features

- 360° continuously pan, 90° in tilt, 180° in auto flip
- Max 128 presets, programmable
- Three-dimensional scan between two presets
- OSD Function
- Tour through presets in groups
- Pelco P or D protocol is identified automatically
- Activity Function
- Auto Park Function
- Proportional Controlling Function
- Scan Precision:  $0.12^{\circ} \pm 0.03^{\circ}$
- Preset Precision:  $\pm 0.2^{\circ}$
- High-intensity PC inside
- Ceiling Mount Included
- AC24V available with additional cost

## JSP-71M18 / JSP-D71M23

### Specification

Model	JSP-71M18	JSP-D71M23
CCD	1/4" Super HAD CCD	1/4" Super HAD CCD
Camera	Sony EX-45CP Color 18x Zoom Camera	Samsung SDM-231 Day/Night Color 23x Zoom Camera
Picture Element	NTSC: 768(H) x 494(V) ; PAL: 752(H) x 582(V)	
Low Sensitivity	0.7Lux	Color: 0.7Lux Black:0.007Lux
Focal Length	4.1~73.8mm	3.84~88.4mm
Resolution	480TVL	
Zoom Ratio	18x	23x
Digital Zoom	12x	10x
Pan/Tilt turn speed	0.12° - 120°/S	
Manual tilt scale	0° - 90°	
Scan scale	360° continuously	
Presets number	Max 128	
Scan precision	0.12° ± 0.03°	
Signal format	PAL/NTSC	
Preset precision	± 0.2°	
S/N ratio	>48dB	
Communication format	RS-485	
Power on	Three options after Self-check (By Menu) Wait for commands / Scan between two presets / Call presets automatically	
Housing material	High-intensity ABS, aging-resistance	
Housing color	Black	
Built-in protocol	Pelco P or D protocol is identified automatically	
Applicable temperature	-10°C ~ 50°C (14°F ~ 122°F)	
Baud rate	1200 / 2400 / 4800 / 9600	
Consumed power	≤ 24W	
Voltage	DC12V	

### Dimension

