

Outdoor PTZ Speed Dome

JSP-72K23

JSP-D72K23



Features


- IP67
- Built-in fan and automatic heater
- Removal Protector
- Intake of metal dome housing is adjustable
- Powerful function ,human menu setup
- Preset characters are programmable
- Proportional controlling function
- Fast address function
- Built-in lens hood is handsome and covert
- Privacy zone masking function , 24 privacy zones can be set
- Mechanism can be installed easily with fast fastening method
- Pan/tilt coordinate display function
- AC24V available with additional cost

JSP-72K23 / JSP-D72K23

Specification

Model	JSP-72K23	JSP-D72K23
CCD	1/4" Super HAD CCD	1/4" Exview HAD CCD
Camera	Samsung SDM-230 Color 23x Zoom Camera	Samsung SDM-231 Day/Night Color 23x Zoom Camera
Picture Element	NTSC: 768(H) x 494(V) ; PAL: 752(H) x 582(V)	
Low Sensitivity	0.7Lux	Color:0.7Lux B/W:0.007Lux
Focal Length	3.84~88.4mm	3.84~88.4mm
Resolution	Color: 540TVL ; B/W: 570TVL	
Electronic Shutter	1/50~120,000 sec.	1/50~1/10,000 sec.
Zoom Ratio	23x	23x
Digital Zoom	10x	10x
Pan speed	0.1°- 240°/S	
Tilt speed	0.1°- 120°/S	
Manual tilt scale	0°- 90°	
Scan scale	360°continuously	
Presets number	Max 128	
Scan precision	0.12°±0.03°	
Signal format	PAL/NTSC	
Preset precision	±0.2°	
S/N ratio	>50dB	
Communication format	RS-485	
White Balance	Auto/Manual	
Power on	Three options after Self-check (By Menu) Wait for commands / Scan between two presets / Call presets automatically	
Built-in protocol	Pelco P or D protocol is identified automatically	
Applicable temperature	-35°C ~ 50°C (-31°F ~ 122°F)	
Baud rate	1200 / 2400 / 4800 / 9600	
Consumed power	≤20W	
Voltage	DC12V	

Dimension



Optional Parts



Pole-mount Bracket
PMB-J903



Wall-mount Bracket
WMB-J912