

# Outdoor PTZ Speed Dome

JSP-72N18

JSP-D72N18



## Features


- 360° continuous pan , 90° in tilt , 180° in auto flip
- Max 128 presets, programmable
- Low speed by manual is widen range, catch on the target accurately
- Auto pan scan
- Three-dimensional scan between two presets
- Call camera menu
- Manual zoom
- Manual/ Auto focus
- Manual/ Auto Iris
- Manual/ Auto black and white switching (Camera self function)
- Focus & Iris speed is adjustable
- Auto/ Manual white balance
- Manual/ Auto backlight compensation
- Tour through presets in groups
- Tour speed is adjustable
- Dwell time is changeable
- Standard RS485 communication
- AC24V available with additional cost

## JSP-72N18 / JSP-D72N18

### Specification

Model	JSP-72N18	JSP-D72N18
CCD	1/4" Super HAD CCD	1/4" Exview HAD CCD
Camera	Sony EX-45CP Color 18x Zoom Camera	Sony EX-480 Day/Night Color 18x Zoom Camera
Picture Element	NTSC: 768(H) x 494(V) ; PAL: 752(H) x 582(V)	
Low Sensitivity	0.7Lux	0.002Lux
Focal Length	34.1~73.8mm	34.1~73.8mm
Resolution	480TVL	
Electronic Shutter	1/50~10,000 sec.	1/3~1/10,000 sec.
Zoom Ratio	18x	18x
Digital Zoom	12x	12x
Pan speed	0.1° - 240°/S	
Tilt speed	0.1° - 120°/S	
Manual tilt scale	0° - 90°	
Scan scale	360° continuously	
Presets number	Max 128	
Scan precision	0.12°±0.03°	
Signal format	PAL/NTSC	
Preset precision	±0.2°	
S/N ratio	>50dB	
Communication format	RS-485	
White Balance	Auto/Manual	
Power on	Three options after Self-check (By Menu) Wait for commands / Scan between two presets / Call presets automatically	
Built-in protocol	Pelco P or D protocol is identified automatically	
Applicable temperature	-35°C ~ 50°C (-31°F ~ 122°F)	
Baud rate	1200 / 2400 / 4800 / 9600	
Consumed power	≤20W	
Voltage	DC12V	

### Dimension



### Optional Parts



Pole-mount Bracket  
**PMB-J903**



Wall-mount Bracket  
**WMB-J912**