

# Outdoor PTZ Speed Dome

JSP-72K23

JSP-D72K23



## Features


- 360° continuous pan, 90° in tilt, 180° in auto flip
- Max 128 presets, programmable
- Low speed by manual is wider range, catch on the target accurately
- Auto pan scan
- Three-dimensional scan between two presets
- Call camera menu
- Manual zoom
- Manual/Auto focus
- Manual/Auto Iris
- Manual/Auto black and white switching (Camera self function)
- Focus & Iris speed is adjustable
- Auto/Manual white balance
- Manual/Auto backlight compensation
- Tour through presets in groups
- Tour speed is adjustable
- Dwell time is changeable
- Standard RS485 communication
- AC24V available with additional cost

## JSP-72N23 / JSP-D72N23

### Specification

Model	JSP-72N23	JSP-D72N23
CCD	1/4" Super HAD CCD	1/4" Exview HAD CCD
Camera	Samsung SDM-230 Color 23x Zoom Camera	Samsung SDM-231 Day/Night Color 23x Zoom Camera
Picture Element	NTSC: 768(H) x 494(V) ; PAL: 752(H) x 582(V)	
Low Sensitivity	0.7Lux	Color:0.7Lux B/W:0.007Lux
Focal Length	3.84~88.4mm	3.84~88.4mm
Resolution	Color: 540TVL ; B/W: 570TVL	
Electronic Shutter	1/50~120,000 sec.	1/50~1/10,000 sec.
Zoom Ratio	23x	23x
Digital Zoom	10x	10x
Pan speed	0.1° - 240°/S	
Tilt speed	0.1° - 120°/S	
Manual tilt scale	0° - 90°	
Scan scale	360° continuously	
Presets number	Max 128	
Scan precision	0.12°±0.03°	
Signal format	PAL/NTSC	
Preset precision	±0.2°	
S/N ratio	>50dB	
Communication format	RS-485	
White Balance	Auto/Manual	
Power on	Three options after Self-check (By Menu) Wait for commands / Scan between two presets / Call presets automatically	
Built-in protocol	Pelco P or D protocol is identified automatically	
Applicable temperature	-35°C ~ 50°C (-31°F ~ 122°F)	
Baud rate	1200 / 2400 / 4800 / 9600	
Consumed power	≤20W	
Voltage	DC12V	

### Dimension



### Optional Parts



Pole-mount Bracket  
**PMB-J903**



Wall-mount Bracket  
**WMB-J912**