

Outdoor PTZ Speed Domes

JSP-72S23

JSP-D72S23

JSP-D72S30



Features


- IP67
- Built-in fan and automatic heater
- Removal Protector
- Intake of metal dome housing is adjustable
- Powerful function ,human menu setup
- Preset characters are programmable
- Proportional controlling function
- Fast address function
- Built-in lens hood is handsome and covert
- Privacy zone masking function , 24 privacy zones can be set
- Mechanism can be installed easily with fast fastening method
- Pan/tilt coordinate display function
- AC24V available with additional cost

JSP-72S23 / JSP-D72S23 / JSP-D72S30

Specification

Model	JSP-72S23	JSP-D72S23	JSP-D72S30
CCD	1/4" Super HAD CCD	1/4" Exview HAD CCD	1/4" Exview HAD CCD
Camera	Samsung SDM-230 Color 23x Zoom Camera	Samsung SDM-231 Day/Night Color 23x Zoom Camera	Samsung SDM-310 Day/Night Color 30x Zoom Camera
Picture Element	NTSC: 768(H) x 494(V) ; PAL: 752(H) x 582(V)		
Low Sensitivity	0.7Lux	Color:0.7Lux B/W:0.007Lux	Color:0.4Lux B/W:0.002Lux
Focal Length	3.84~88.4mm	3.84~88.4mm	3.3~99mm
Resolution	Color: 540TVL ; B/W: 570TVL		
Electronic Shutter	1/50~120,000 sec.	1/50~1/10,000 sec.	1/3~1/10,000 sec
Zoom Ratio	23x	23x	30x
Digital Zoom	10x	10x	10x
Pan speed	0.1°- 240°/S		
Tilt speed	0.1°- 120°/S		
Manual tilt scale	0°- 90°		
Scan scale	360°continuously		
Presets number	Max 128		
Scan precision	0.12°±0.03°		
Signal format	PAL/NTSC		
Preset precision	±0.2°		
S/N ratio	>50dB		
Communication format	RS-485		
White Balance	Auto/Manual		
Power on	Three options after Self-check (By Menu) Wait for commands / Scan between two presets / Call presets automatically		
Built-in protocol	Pelco P or D protocol is identified automatically		
Applicable temperature	-35°C ~ 50°C (-31°F ~ 122°F)		
Baud rate	1200 / 2400 / 4800 / 9600		
Consumed power	≤20W		
Voltage	DC12V		

Dimension



Optional Parts



Pendant Bracket
PMB-J902



Wall-mount Bracket
with Power Box
WMB-J908



Wall-mount
Bracket
WMB-J909