

Outdoor PTZ Speed Dome

JSP-D72K26

JSP-D72K30



Features


- IP67
- Built-in fan and automatic heater
- Removal Protector
- Intake of metal dome housing is adjustable
- Powerful function ,human menu setup
- Preset characters are programmable
- Proportional controlling function
- Fast address function
- Built-in lens hood is handsome and covert
- Privacy zone masking function , 24 privacy zones can be set
- Mechanism can be installed easily with fast fastening method
- Pan/tilt coordinate display function
- AC24V available with additional cost

JSP-D72K26 / JSP-D72K30

Specification

Model	JSP-D72K26	JSP-D72K30
CCD	1/4" Exview HAD CCD	
Camera	Sony EX-980P Day/Night Color 26x Zoom Camera	Samsung SDM-310 Day/Night Color 30x Zoom Camera
Picture Element	NTSC: 768(H) x 494(V) ; PAL: 752(H) x 582(V)	
Low Sensitivity	Color:1.0Lux B/W: 0.001Lux	Color:0.4Lux B/W: 0.002Lux
Focal Length	3.5~91.0mm	3.3~99mm
Resolution	520TVL	
Electronic Shutter	1/50~1/10,000 sec.	
Zoom Ratio	26x	30x
Digital Zoom	10x	10x
Pan speed	0.1° - 240°/S	
Tilt speed	0.1° - 120°/S	
Manual tilt scale	0° - 90°	
Scan scale	360° continuously	
Presets number	Max 128	
Scan precision	0.12°±0.03°	
Signal format	PAL/NTSC	
Preset precision	±0.2°	
S/N ratio	>50dB	
Communication format	RS-485	
White Balance	Auto/Manual	
Power on	Three options after Self-check (By Menu) Wait for commands / Scan between two presets / Call presets automatically	
Built-in protocol	Pelco P or D protocol is identified automatically	
Applicable temperature	-35°C ~ 50°C (-31°F ~ 122°F)	
Baud rate	1200 / 2400 / 4800 / 9600	
Consumed power	≤20W	
Voltage	DC12V	

Dimension



Optional Parts



Pole-mount
Bracket
PMB-J903



Wall-mount
Bracket
WMB-J912