

# Outdoor 100M IR Speed Dome

JSP-D83F18

JSP-D83F26



## Features

- Multi-Protocol Decoder Built-in
- Auto/Manual White Balance Adjustable
- 12x Digital Zoom
- 0~360° Panning Range
- 0~80°/sec.Panning Speed
- -90°~+90° Tilt Range
- 0~40°/sec. Tilt Speed
- 128 Programmable Preset Points
- 6 Programmable Cruising Tracks
- RS-485 Port
- Support Pelco-D, Pelco-P Protocols
- IR-LED Built-in Range Up to 100 Meter
- IP 66 Weatherproof Design
- With Heater & Blower Built-in
- With Wiper Build-in
- AC 24V

## JSP-D83F18 / JSP-D83F26

### Specification

| Model                    | JSP-D83F18   | JSP-D83F26                    |
|--------------------------|--|-------------------------------|
| CCD                      | 1/4" Sony ExView HAD CCD   |                               |
| Camera                   | Sony EX-480 Camera   | Sony EX-980 Camera            |
| Picture Element          | NTSC: 768(H) x 494(V) ; PAL: 752(H) x 582(V)                     |                               |
| Low Sensitivity          | 0.7 Lux @F1.2 / 0 Lux with IR                                    | 1.0 Lux @F1.6 / 0 Lux with IR |
| Focal Length             | 4.1mm~ 73.8mm 18x Zoom Lens                                      | 3.5mm~91.0mm 26x Zoom Lens    |
| Resolution               | 480TVL   |                               |
| Electronic Shutter       | 1/3 ~ 1/10000 sec.   |                               |
| Zoom Ratio               | 18x  | 26x                           |
| Digital Zoom             | 12x Digital Zoom   | 12x Digital Zoom              |
| Pan speed                | 0 ~ 80° /sec.  |                               |
| Tilt speed               | 0 ~ 40° /sec.  |                               |
| Manual tilt scale        | -90° ~ 90°   |                               |
| Scan scale               | 360°continuously   |                               |
| Presets Point            | Max. 128 Preset Points for Pan, Tilt & Zoom Lens                 |                               |
| Auto Tracking Mode       | 6 Cruising Tracks  |                               |
| SRemote Control          | RS-485 Port with 2400/4800/9600/19200 bps Baud Rate Transmission |                               |
| Protocol Decoder         | Multi-Protocol Decoder Built-in                                  |                               |
| Protocol Support         | Supports Pelco-D/2400, Pelco-P/9600 and Other Protocols          |                               |
| Infrared LED             | IR-LED Built-in for Up to 100 Meter of Illuminating Range        |                               |
| Video Output             | 1.0 Vp-p Composite Video ; 75 Ohm                                |                               |
| Installation Environment | IP 66 Weatherproof Design with Heater, Blower & Wiper Built-in   |                               |
| Operating Temperature    | -35°C ~ 50°C (-31°F ~ 122°F)                                     |                               |
| Power Supply             | AC24V  |                               |
| Weight                   | N.W.: 6.0 Kgs ; G.W.: 7.5 Kgs                                    |                               |

### Optional Parts



Wall-mount  
Bracket  
**JS-B27**



Shock Absorber  
**JS-TC2600**