

PA-8904X / PA-8908X

4 / 8 CH H.264 Hexaplex Network DVR



Specifications

Model	PA-8904X	PA-8908X
Operation System	Embedded Linux	
Compression Format	H.264	
Video input/output	4 channel BNC input/1 channel BNC output	8Ch BNC Input/1Ch BNC Output, 1Ch VGA output
Audio input/output	4 channel BNC input/1 channel BNC output	1Ch RCA Input/1Ch RCA Output
Displaying Speed	NTSC:120 FPS(4*30 FPS) PAL:100 FPS(4*25 FPS)	NTSC:240 FPS(8*30 FPS) PAL:200 FPS(8*25 FPS)
Recording Speed	NTSC:120 FPS(4*30 FPS) PAL:100 FPS(4*25 FPS)	NTSC:240 FPS(8*30 FPS) PAL:200 FPS(8*25 FPS)
Operating Mode	Record,Replay,Live display,Backup,Network	Record, Replay, Live Display, Backup, Network
Display mode	PIP,Full screen,Quad	PIP, Full Screen, Quad, 8Ch Split-Screen
Recording Resolution	NTSC:352x240(CIF) 704x240(Half D1) 704x480(D1) PAL:352x288(CIF) 704x288(Half D1) 704x576(D1)	
Alarm input/output	4 channel alarm input/1 channel alarm output	8 channel alarm input/1 channel alarm output
Replay	Support multi-ch replay at the same time	
HDD	1 SATA HDD,Max 2TB	
Recording Mode	Manual,Alarm,Motion Detection,Scheduled	
Network	1/10 Base-T,TCP/IP,UDP,NTP,DHCP,DDNS	
Mouse	USB	
Backup	USB backup	
PTZ	RS-485,zoom,preset points,control	
Alarming Mode	Sensing,Motion detection,Video Loss	
Power Supply	DC 12V,5A	
Dimensions	200(L)*163(W)*70(H)mm	

Feature

- Standalone H.264 Compression
- Built-in 7 inch LCD monitor
- 4 / 8 CH BNC Video input, 1 CH BNC Video output
- Real time support D1
- Video and Audio synchronously
- Support PTZ control RS-485
- Built-in RS-485 port

Dimension(unit:mm)



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jsctv.com.tw

