

# PA-8916NV

16Ch. H.264 Stand-Alone DVR



## Feature

- Standalone H.264 Compression
- Network Function
- 16Ch BNC Video input, 1Ch BNC Video output, 1Ch VGA output
- Support D1 Real-time Recording
- Video and Audio synchronously
- Support PTZ control RS-485
- Built-in RS-485 port

## Dimension(unit:mm)

## Specifications

Model	PA-8916NV
Operation System	Embedded Linux
Compression Format	H.264
Video input/output	16Ch BNC input/1Ch BNC output, 1Ch VGA output
Audio input/output	4Ch RCA input/1Ch RCA output
Displaying Speed	NTSC:480 FPS(16*30 FPS ) PAL:400 FPS(16*25 FPS )
Recording Speed	NTSC:480 FPS(16*30 FPS ) PAL:400 FPS(16*25 FPS )
Operating Mode	Record,Replay,Live display,Backup,Network
Display mode	PIP, Full Screen, Quad, 16Ch Split-Screen
Recording Resolution	NTSC:352x240(CIF) 704x240(Half D1) 704x480(D1) PAL:352x288(CIF) 704x288(Half D1) 704x576(D1)
Alarm input/output	16 channel alarm input/1 channel alarm output
Replay	Support multi-ch replay at the same time
HDD	2 SATA HDDs, Max 2TB Capacity
Recording Mode	Manual,Alarm,Motion Detection,Scheduled
Network	1/10 Base-T,TCP/IP,UDP,NTP,DHCP,DDNS
Mouse	USB
Backup	USB backup
PTZ	RS-485, zoom, preset points, control
Alarming Mode	Sensing, Motion detection, Video Loss
Power Supply	DC 12V, 5A
Dimensions	380(L)*275(W)*70(H)mm



J&S United Technology Corp.  
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan  
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338  
www.jsctv.com.tw

