

# Weatherproof IR Color Cameras



## ► Features

- 1/3" Sharp Color CCD Sensor
- NTSC:512x492/PAL:512x582 Pixels
- 420 TV Lines
- 0.1 Lux / F1.2 ; 0 Lux(IR On)
- High quality picture, aesthetic and easy to install
- Auto Gain Control (AGC)
- Auto exposure (AE)
- Aperture Correction
- Anti color rolling
- Built-in 6.0mm Lens
- DC 12V

## SKC-31D123

## ► Specification

<b>Model</b>	SKC-31D123
<b>CCD</b>	1/3" Sharp CCD
<b>Effective Pixels</b>	NTSC: 512(H) x 492(V) ; PAL: 512 (H) x 582(V)
<b>Signal System</b>	PAL/NTSC
<b>Horizontal Resolution</b>	420 TV Lines
<b>Lens</b>	6.0mm (standard). 3.6mm, 4.3mm, 8mm (option)
<b>Sync. System</b>	Internal
<b>Minimum Illumination</b>	0.1 Lux / F1.2 ; 0 Lux(IR On)
<b>S/N Ratio</b>	More than 48dB
<b>Electronic Shutter</b>	Auto and up to 1/100,000
<b>White Balance</b>	MCT-AWB (Multi Color Temperature AWB)
<b>Backlight Compensation</b>	Auto
<b>Auto Gain Control</b>	Auto
<b>Aperture Correction</b>	2H Mode of H.V aperture correction
<b>Water Proof Level</b>	IP66
<b>IR LED</b>	20
<b>Video Output</b>	1 Vp-p, 75 Ohm
<b>Power Supply</b>	DC 12V (-/+10%)
<b>Power Consumption</b>	150mA ±10% IR 250mA ±10% under DC 12V
<b>Operating Temperature</b>	-10°C ~ 45°C
<b>Dimension L*W</b>	52mm*71mm
<b>Weight</b>	410g