

# Weatherproof IR Color Cameras



## ► Features

- 1/3" Color CCD Sensor
- 420/480 TV Lines
- High quality picture, aesthetic and easy to install
- Auto Gain Control (AGC)
- Auto exposure (AE)
- Aperture Correction
- Anti color rolling
- Built-in 6.0mm Lens
- DC 12V

## SKC-31D123 / SKC-31D134

## ► Specification

Model	SKC-31D123	SKC-31D125
CCD	1/3" Sharp CCD	1/3" Sony CCD
Effective Pixels	NTSC: 512(H) x 492(V) PAL: 512 (H) x 582(V)	NTSC: 711(H) x 492(V) PAL: 753 (H) x 582(V)
Signal System	PAL/NTSC	
Horizontal Resolution	420 TV Lines	480 TV Lines
Lens	6.0mm (standard). 3.6mm, 4.3mm, 8mm (option)	
Sync. System	Internal	
Minimum Illumination	0.1 Lux / F1.2 ; 0 Lux(IR On)	0.2 Lux / F1.2 ; 0 Lux(IR On)
S/N Ratio	More than 48dB	
Electronic Shutter	Auto and up to 1/100,000	
White Balance	MCT-AWB (Multi Color Temperature AWB)	
Backlight Compensation	Auto	
Auto Gain Control	Auto	
Aperture Correction	2H Mode of H.V aperture correction	
Water Proof Level	IP66	
IR LED	20	
Video Output	1 Vp-p, 75 Ohm	
Power Supply	DC 12V (-/+10%)	
Power Consumption	150mA ±10% IR 250mA ±10% under DC 12V	
Operating Temperature	-10°C ~ 45°C	
Dimension L*W	52mm*71mm	
Weight	410g	