

20M IR Cameras

SKC-31F432

SKC-31F436



► Features

- SKC-31F432:
 - 1/3" SONY SUPER HAD CCD
 - 420 TV Lines / 0.5Lux @F1.2
- SKC-31F436:
 - 1/3" SONY SUPER HAD CCD
 - SONY 10-bit HQ1 DSP
 - 540 TV Lines / 0.8Lux @F1.2
- IP66 Weatherproof Housing with Bracket & Sunshield
- 24 Infrared Led(Φ5mm)
- 20 meters IR Distance
- Built-in 3.6mm MTV Lens
- DC12V 320mA

SKC-31F432 / SKC-31F436

► Specification

Model	SKC-31F432	SKC-31F436
CCD	1/3" SONY SUPER HAD CCD	1/3" SONY SUPER HAD CCD
DSP	SONY DSP	SONY 10-bit HQ1 DSP
Effective pixels	PAL:500(H)x582(V) NTSC:510(H)x492(V)	PAL:752(H)x582(V) NTSC:768(H)x494(V)
Signal System	PAL/NTSC	
Horizontal Resolution	420 TV Lines	540 TV Lines
Lens	3.6mm MTV Lens	
Sync. System	Inter line Synchronization	
Minimum Illumination	0.5Lux @F1.2, 0Lux(IR On)	0.8Lux @F1.2, 0Lux(IR On)
S/N Ratio	More than 48dB(AGC OFF)	
Electronic Shutter	1/50(1/60)~1/100,000sec.	
White Balance	Auto	
Backlight Compensation	Auto	
Auto Gain Control	On/Off Switchable	
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)	
Power Sourcing	DC12V	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F) RH95%(MAX)	
Dimension	inner(D)61xouter(D)49.3x(H)114.7	

► Dimension

