

Color 20M IR Cameras

SKC-31K321

SKC-31K323

SKC-31K332

SKC-31K334



Features

- SKC-31K321 :
1/4" Sharp CCD
420 TV Lines / 0.8Lux
- SKC-31K323 :
1/3" Sharp CCD
420 TV Lines / 0.8Lux
- SKC-31K332 :
1/3" Sony Super HAD CCD
420 TV Lines / 0.5Lux
- SKC-31K334 :
1/3" Sony Super HAD CCD
480 TV Lines / 0.8Lux
- Automatic Gain Control & BLC
- 24 High Output IR LED's W/45 Range
- Unique Design Suitable For Indoor/Outdoor
- Weather Resistance IP57 Case
- DC 12V

SKC-31K321 / SKC-31K323 / SKC-31K332 /SKC-31K334

Specification

Model	SKC-31K321	SKC-31K323	SKC-31K332	SKC-31K334
CCD	1/4" Sharp CCD	1/3" Sharp CCD	1/3" Sony CCD	1/3" Sony Super HAD CCD
Effective pixels	PAL:542(H)X582(V) NTSC:512(H)X492(V)	PAL:542(H)X582(V) NTSC:512(H)X492(V)	PAL:532(H)X597(V) NTSC:537(H)X505(V)	PAL:752(H)X582(V) NTSC:768(H)X494(V)
Signal System	PAL/NTSC			
Horizontal Resolution	420 TV Lines	420 TV Lines	420 TV Lines	480 TV Lines
Lens	3.6mm Lens			
Sync. System	Internal			
Minimum Illumination	0.8Lux/F2.0(LED OFF) ; 0Lux (LED ON)	0.8Lux/F2.0(LED OFF) ; 0Lux (LED ON)	0.5Lux/F2.0(LED OFF) ; 0Lux (LED ON)	0.8Lux/F2.0(LED OFF) ; 0Lux (LED ON)
S/N Ratio	More than 48dB			
Electronic Shutter	1/50~1/100,000sec(PAL),1/60~1/100,000sec(NTSC)			
White Balance	Auto ATW 2500-9500°K			
Gain Control	AGC			
BLC	Auto			
IR-LED	24 units 850nm infrared LED, More than 10,000 Hours			
Distance	20 Meter			
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)			
Power Supply	DC 12V			
Power Consumption	IR on: 300mA, IR off: 80mA			
Operation Temperature	Operating: -20 ~ + 55 °C , Storage: -30 ~ + 80 °C , Humidity:0~95%RH			
Weight	460g			

Dimension

