

IP66 Color 20M IR Cameras

SKC-31KR21

SKC-31KR23

SKC-31KR32

SKC-31KR34



Features

- SKC-31KR21 :
1/4" Sharp CCD
420 TV Lines / 0.8Lux
- SKC-31KR23 :
1/3" Sharp CCD
420 TV Lines / 0.8Lux
- SKC-31KR32 :
1/3" Sony Super HAD CCD
420 TV Lines / 0.5Lux
- SKC-31KR34 :
1/3" Sony Super HAD CCD
480 TV Lines / 0.8Lux
- Automatic Gain Control & BLC
- 30pcs Ø5 IR-LEDs
- Unique Design Suitable For Indoor/Outdoor
- Weather Resistance IP66 Case
- DC 12V

SKC-31KR21 / SKC-31KR23 / SKC-31KR32 / SKC-31KR34

Specification

Model	SKC-31KR21	SKC-31KR23	SKC-31KR32	SKC-31KR34
CCD	1/4" Sharp CCD	1/3" Sharp CCD	1/3" Sony CCD	1/3" Sony Super HAD CCD
Effective pixels	PAL:542(H)X582(V) NTSC:512(H)X492(V)	PAL:542(H)X582(V) NTSC:512(H)X492(V)	PAL:532(H)X597(V) NTSC:537(H)X505(V)	PAL:752(H)X582(V) NTSC:768(H)X494(V)
Signal System	PAL/NTSC			
Horizontal Resolution	420 TV Lines	420 TV Lines	420 TV Lines	480 TV Lines
Lens	6.0mm Lens			
Sync. System	Internal			
Minimum Illumination	0.8Lux/F2.0(LED OFF) 0Lux (LED ON)	0.8Lux/F2.0(LED OFF) 0Lux (LED ON)	0.5Lux/F2.0(LED OFF) 0Lux (LED ON)	0.8Lux/F2.0(LED OFF) 0Lux (LED ON)
S/N Ratio	More than 48dB			
Electronic Shutter	1/50~1/100,000sec(PAL), 1/60~1/100,000sec(NTSC)			
White Balance	Auto ATW 2500-9500 ° K			
AGC	Adjustable			
BLC	Adjustable			
IR-LED	30pcs Ø5 IR-LEDs			
Distance	20 Meter			
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)			
Power Supply	DC 12V			
Operation Temperature	-10°C ~ 50°C (14°F ~ 122°F)			
Weight				