

# Color 10M IR Cameras

SKC-31KS21

SKC-31KS23

SKC-31KS32



## ► Features

- SKC-31KS21: 1/4" Sharp CCD  
420 TV Lines / 0.8Lux @F1.2
- SKC-31KS23: 1/3" Sony CCD  
420 TV Lines / 0.8Lux @F1.2
- SKC-31KS32: 1/3" Sony CCD  
420 TV Lines / 0.5Lux @F1.2
- DSP technology
- Automatic Gain Control & BLC
- 12 High Output IR LED's W/45' Range
- Unique Design Suitable For Indoor/ Outdoor
- Built-in 3.6mm Lens, excellent Value
- DC12V

## SKC-31KS21 / SKC-31KS23 / SKC-31KS32

### ► Specification

Model	SKC-31KS21	SKC-31KS23	SKC-31KS32
CCD	1/4" Sharp CCD	1/3" Sharp CCD	1/3" Sony CCD
Effective pixels	PAL:512(H)x582(v) NTSC:512(H)x492(v)	PAL:512(H)x582(v) NTSC:512(H)x492(v)	PAL:500(H)x582(v) NTSC:510(H)x492(v)
Signal System	PAL/NTSC		
Horizontal Resolution	420 TV Lines	420 TV Lines	420 TV Lines
Lens	3.6mm Lens		
Sync. System	Internal		
Minimum Illumination	0.8Lux @F1.2	0.8Lux @F1.2	0.5Lux @F1.2
S/N Ratio	More than 48dB(AGC OFF)		
Electronic Shutter	1/50(1/60)—1/100,000(Sec.)		
White Balance	Auto ATW 2500-9500 ° K		
Backlight Compensation	Auto		
Gain Control	AGC		
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)		
IR LED	12 units 850nm infrared LED, Up to 15 meters (Subject to IR reflection conditions )		
Power Sourcing	DC12V		
Power Consumption	IR on: 300mA, IR off: 120mA		
Operating Temperature	Operating: -20 ~ + 55 °C , Storage: -30 ~ + 80 °C , Humidity:0~95%RH		
Weight	370g		
Dimension(mm)	53.5 (W) x 130 (H) x 76.5(L)		

### ► Dimension

