

Color 25M IR Camera



► Features

- 1/3" SONY Super HAD CCD
- IP66 Waterproof Housing with Bracket & Sunshield
- High Resolution 540 TVL 0.5 LUX
- Built-in 4-9mm Motorized Lens
- 36 IR LEDS, Up to 25M IR distance
- Dual Glass Technology
- With Remote Control(RS485) Optional



SKC-33MF521 / SKD-33MF532 / SKD-33MF536

► Specification

Model	SKC-33MF521	SKC-33MF532	SKC-33MF536
CCD	1/4" Sharp Color CCD Sensor	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD
Effective pixels	NTSC: 512(H) x 492(V) PAL: 512 (H) x 582(V)	NTSC: 537(H)x505(V) PAL: 537(H)x597(V)	NTSC:811(H)x508(V) PAL:795(H)x596(V)
Signal System	NTSC/PAL		
Horizontal Resolution	420 TV Lines	420 TV Lines	540 TV Lines
Lens	4-9mm Motorized Lens		
Sync. System	Inter line Synchronization		
Minimum Illumination	1LUX/F1.2 0LUX (LED ON)	0.5LUX/F1.2 0LUX (LED ON)	0.5LUX/F1.2 0LUX (LED ON)
S/N Ratio	More than 48dB (AGC off)		
Electronic Shutter	PAL: 1/50~1/100,000 sec		
White balance	Auto White Balance(AWB)		
BLC	Back Light Compensation (Auto)		
IR Distance	25 Meter		
Infrared Led	36 Infrared Led(Φ5mm)		
Video Output	Composite Video Output(1.0Vp-p 75ΩTerminated)		
Power Sourcing	DC12V		
Operating Temperature	-10~+50°C RH95%Max		