

Color 35M IR Cameras



► Features

- 1/3" SONY Super HAD CCD
- 420/540 TVL
- 1.0/0.5LUX
- Built-in 4-9mm Motorized Lens
- 48 IR LEDS, Up to 35M IR distance
- Waterproof
- With Remote Control(RS485) Optional



SKC-33MF721 / SKC-33MF732 / SKC-33MF736

► Specification

| Model | SKC-33MF721 | SKC-33MF732 | SKC-33MF736 |
|-----------------------|---|---|---|
| CCD | 1/4" Sharp Color CCD Sensor | 1/3" Sony Super HAD CCD | 1/3" Sony Super HAD CCD |
| Effective pixels | NTSC: 512(H) x 492(V) PAL: 512 (H) x 582(V) | NTSC: 537(H)x505(V) PAL: 537(H)x597(V) | NTSC:811(H)x508(V) PAL:795(H)x596(V) |
| Signal System | NTSC/PAL | | |
| Horizontal Resolution | 420 TV Lines | 420 TV Lines | 540 TV Lines |
| Lens | 4-9mm Motorized Lens(Optional: 3.7-14.8mm Motorized Lens) | | |
| Sync. System | Inter line Synchronization | | |
| Minimum Illumination | 1LUX/0LUX (LED ON) | 0.5LUX/0LUX (LED ON) | 0.5LUX/0LUX (LED ON) |
| S/N Ratio | More than 48dB (AGC off) | | |
| Electronic Shutter | PAL: 1/50~1/100,000 sec | | |
| White balance | Auto White Balance(AWB) | | |
| BLC | Back Light Compensation (Auto) | | |
| IR Distance | 35 Meter | | |
| Infrared Led | 48 Infrared Led(Φ5mm) | | |
| Video Output | Composite Video Output(1.0Vp-p 75ΩTerminated) | | |
| Power Sourcing | DC12V 450mA | | |
| Operating Temperature | -10~+50°C RH95%Max | | |

► Dimension

