

# Color 35M IR Cameras



Optional

## ► Features

- 1/3" SONY Super HAD CCD
- 420/540 TVL
- 1.0/0.5LUX
- Built-in 4-9mm Motorized Lens
- 48 IR LEDS, Up to 35M IR distance
- Waterproof
- With Remote Control(RS485) Optional

## SKC-33MF721 / SKC-33MF732 / SKC-33MF736

## ► Specification

| Model                 | SKC-33MF721                                    | SKC-33MF732                               | SKC-33MF736                             |
|-----------------------|--|---|---|
| CCD                   | 1/4" Sharp Color CCD Sensor                    | 1/3" Sony Super HAD CCD                   | 1/3" Sony Super HAD CCD                 |
| Effective pixels      | NTSC: 512(H) x 492(V)<br>PAL: 512 (H) x 582(V) | NTSC: 537(H)x505(V)<br>PAL: 537(H)x597(V) | NTSC:811(H)x508(V)<br>PAL:795(H)x596(V) |
| Signal System         | NTSC/PAL                                       |   |   |
| Horizontal Resolution | 420 TV Lines                                   | 420 TV Lines                              | 540 TV Lines                            |
| Lens                  | 4-9mm Motorized Lens                           |   |   |
| Sync. System          | Inter line Synchronization                     |   |   |
| Minimum Illumination  | 1LUX/0LUX (LED ON)                             | 0.5LUX/0LUX (LED ON)                      | 0.5LUX/0LUX (LED ON)                    |
| S/N Ratio             | More than 48dB (AGC off)                       |   |   |
| Electronic Shutter    | PAL: 1/50~1/100,000 sec                        |   |   |
| White balance         | Auto White Balance(AWB)                        |   |   |
| BLC                   | Back Light Compensation (Auto)                 |   |   |
| IR Distance           | 35 Meter                                       |   |   |
| Infrared Led          | 48 Infrared Led(Φ5mm)                          |   |   |
| Video Output          | Composite Video Output(1.0Vp-p 75ΩTerminated)  |   |   |
| Power Sourcing        | DC12V 450mA                                    |   |   |
| Operating Temperature | -10~+50°C RH95%Max                             |   |   |

## ► Dimension

