

Fire Sprinkler Covert Cameras

SKC-43F232



SKC-43F236



► Features

- SKC-43F232:
 - 1/3" SONY SUPER HAD CCD
 - 420 TV Lines / 0.5Lux @F1.2
- SKC-43F236:
 - 1/3" SONY SUPER HAD CCD
 - SONY 10-bit HQ1 DSP
 - 530 TV Lines / 0.8Lux @F1.2
- DSP technology
- BLC, AES, AGC, AWB
- Built-in 3.7mm Pinhole Lens, excellent Value
- DC12V

SKC-43F232 / SKC-43F236

► Specification

Model	SKC-43F232	SKC-43F236
CCD	1/3" SONY SUPER HAD CCD	
DSP	Sony DSP	Sony 10-bit HQ1 DSP
Signal System	PAL/NTSC	
Effective Pixels	PAL: 500(H) x 582 (V) NTSC: 510 (H) x 492 (V)	PAL:752(H)x582(V) NTSC:768(H)x494(V)
Horizontal Resolution	420TV line	530 TV Lines
Min. Illumination	0.5Lux@F1.2	0.8Lux @F1.2
Sync. System	Inter line Synchronizaton	
S/N Ratio	More than 48dB(AGC OFF)	
Gamma Correction	0.45	
Video Output	1.0Vp-p, 75 Ohm	
Electronic Shutter	1/50(1/60)~1/100,000(Sec.)	
BLC	Auto	
White Balance	Auto	
Lens	3.7mm Pinhole Len MTV	
Power Supply	DC12V	
Work Temperature	-10°C ~ 50°C (14°F ~ 122°F) RH95%Max	
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F) RH95%Max	
Net Weight	280g	

► Dimension

