

# Corner-Mount Color Camera

SKC-43KC32



## ► Features

- 1/3" Sony CCD
- 420 TV Lines
- 0.5Lux@F1.2
- Built-in Pre-Amp Audio
- Automatic Gain Control & BLC
- 12 High Output IR LED's W/60' Range
- Built-in Lens. Excellent Value
- Photocell Turns on IR LED's at 10 Lux
- DC 12V

## SKC-43KC32

### ► Specification

Model	SKC-43KC32
CCD	1/3" Sony CCD
Signal System	PAL/NTSC
Effective Pixels	NTSC: 512 x 492, PAL: 512 x 582
Horizontal Resolution	420TVL
Min. Illumination	0.5Lux@F1.2
Sync. System	Internal Synchronization
S/N Ratio	More than 48dB
Gamma Correction	0.45
Video Output	1.0Vp-p, 75 Ohm
Electronic Shutter	Auto: 1/50(1/60) ~ 1/100,000 sec.
Gain Control	AGC
BLC	Auto
IR LED	12 units 850nm infrared LED
IR Distance	12meters (Subject to IR reflection conditions )
IR Status	IR on: Under 10 Lux, by PT auto control, More than 10,000 Life Hours
White Balance	Auto ATW 2500-9500 ° K
Lens	3.6mm Lens
Power Supply	DC12V, 500mA
Power Consumption	IR on: 300mA, IR off: 120mA
Work Temperature	Operating: -20 ~ + 55 °C , Storage: -30 ~ + 80 °C , Humidity:0~95%RH
Net Weight	130g

### ► Dimension

