

PIR Covert Cameras



Features

- 1/4" Sharp CCD
- 420TVL
- 0.5Lux@F1.2
- with 3.7mm Pinhole Lens
- Automatic Electronic Shutter
- Automatic Gain Control & BLC
- Auto White Balance
- DC 12V

SKC-43KB32

- 1/3" Sony Super HAD CCD
- 420TVL
- 0.5Lux@F1.2
- with 3.7mm Pinhole Lens
- Automatic Electronic Shutter
- Automatic Gain Control & BLC
- Auto White Balance
- DC 12V

SKC-43KS21 / SKC-43KS32

Specification

Model	SKC-43KS21	SKC-43KS32
CCD	1/4" Sharp CCD	1/3" Sony Super HAD CCD
Signal System	PAL/NTSC	
Effective Pixels	PAL:512(H)x582(v) NTSC:542(H)x492(v)	PAL:537(H)x597(v) NTSC:537(H)x505(v)
Horizontal Resolution	420TVL	
Min. Illumination	0.5Lux@F1.2	
Sync. System	Internal	
S/N Ratio	More than 48dB	
Gamma Correction	0.45	
Video Output	1.0Vp-p, 75 Ohm	
Gain Control	Auto	
BLC	Auto	
White Balance	Auto	
Lens	3.7mm Pinhole Lens	
Power Supply	DC12V	
Power Consumption	110mA	
Work Temperature	-10°C ~ 50°C (14°F ~ 122°F)	
Dimension	33(H)x104(L)mm	
Net Weight	190g	

Dimension

