

Fixed Dome Cameras

SKD-20A421

SKD-20A432



Features

- SKD-20A421:
1/4" Sharp CCD
420 TV Lines / 0.05Lux @F1.2
- SKD-20A432 :
1/3" SONY CCD
420 TV Lines / 0.5Lux @F1.2
- Auto Tracking White Balance
- Auto Gain Control
- Backlight Compensation
- Compact and Beautiful design
- DC12V

SKD-20A421 / SKD-20A432

Specification

Model	SKD-20A421	SKD-20A432
CCD	1/4" Sharp CCD	1/3" SONY CCD
Effective pixels	PAL:500(H)x582(v) NTSC:510(H)x492(v)	PAL:500(H)x582(v) NTSC:510(H)x492(v)
Signal System	PAL/NTSC	
Horizontal Resolution	420 TV Lines	
Lens	3.6mm lens	
Sync. System	Internal	
Minimum Illumination	0.5Lux@F1.2	0.1Lux@F1.2
S/N Ratio	More than 48dB(AGC OFF)	
Electronic Shutter	1/50(1/60)—1/100,000(Sec.)	
White Balance	Auto Tracking White Balance	N/A
AGC	Auto	
Backlight Compensation	Auto	
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)	
Power Sourcing	DC12V/500mA	
Power Consumption	<2.8W	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F) / RH85%(MAX)	
Weight	350g	

Dimension

