

# Fixed Dome Cameras

SKD-20C521

SKD-20C523



## Features

- SKD-20C521:  
1/4" SHARP CCD  
420 TV Lines / 1.0Lux@F1.2
- SKD-20C523:  
1/3" SHARP CCD  
420 TV Lines / 0.8Lux@F1.2
- DSP technology
- S/N Ratio more than 48dB
- Build in 3.6mm fixed lens
- DC12V, low consumption

## SKD-20C521 / SKD-20C523

### Specification

Model	SKD-20C521	SKD-20C523
CCD	1/4" SHARP CCD	1/3" SHARP CCD
Effective pixels	PAL:512(H)x582(v) NTSC:512(H)x492(v)	PAL:512(H)x582(v) NTSC:512(H)x492(v)
Horizontal Resolution	420 TV Lines	420 TV Lines
Lens	3.6mm Lens	
Sync. System	Internal Synchronization	
Minimum Illumination	1.0Lux@F1.2	0.8Lux@F1.2
S/N Ratio	More than 48dB	
Electronic Shutter	1/50(1/60)—1/100,000(Sec.)	
White Balance	Auto Tracking White Balance	
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)	
Power Sourcing	DC12V/120mA	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F) / RH95%(MAX)	
Weight	500g	
Dimension	118(Dia.) * 120mm (H)	

### Dimension

