

Fixed Dome Cameras

SKD-20K412

SKD-20K421

SKD-20K432



Features

- SKD-20K412:
 - 1/3" Sony B/W CCD
 - 420 TV Lines / 0.05Lux@F1.2
- SKD-20K421:
 - 1/4" Sharp CCD
 - 420 TV Lines / 0.5Lux@F1.2
- SKD-20K432:
 - 1/3" Sony CCD
 - 420 TV Lines / 0.8Lux@F1.2
- Built-in 3.6mm Lens
- BLC and AGC
- Auto White Balance
- DC 12V

SKD-20K412 / SKD-20K421 / SKD-20K432

Specification

Model	SKD-20K412	SKD-20K421	SKD-20K432
CCD	1/3" Sony CCD	1/4" Sharp CCD	1/3" Sony CCD
Effective pixels	CCIR:537(H)x597(V) EIA:537(H)x505(V)	PAL:537(H)x597(V) NTSC:537(H)x505(V)	PAL:537(H)x597(V) NTSC:537(H)x505(V)
Signal System	EIA/CCIR	PAL/NTSC	PAL/NTSC
Horizontal Resolution	420 TV Lines		
Lens	3.6mm lens		
Sync. System	Internal		
Minimum Illumination	0.05Lux/F1.2	0.5Lux/F1.2	0.8Lux/F1.2
S/N Ratio	More than 48dB(AGC OFF)		
Electronic Shutter	1/50(1/60)—1/100,000(Sec.)		
White Balance	---	ATW/AWC Switchable	ATW/AWC Switchable
Backlight Compensation	ON/OFF Switchable		
Gain Control	AGC ON/OFF Switchable		
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)		
Power Sourcing	DC12V ±1V/150mA		
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F) / RH85%(MAX)		