

Fixed Dome Cameras

SKD-20KB21

SKD-20KB23

SKD-20KB32

SKD-20KB32H



Features

- SKD-20KB21:
1/4" Sharp CCD
420 TV Lines / 0.5Lux@F1.2
- SKD-20KB23:
1/3" Sharp CCD
420 TV Lines / 0.2Lux@F1.2
- SKD-20KB32:
1/3" Sony Super HAD CCD
420 TV Lines / 0.5Lux@F1.2
- SKD-20KB32H:
1/3" Sony Super HAD CCD
450 TV Lines / 0.5Lux@F1.2
- Built-in 3.6mm Lens
- BLC and AGC
- Auto White Balance
- DC 12V

SKD-20KB21 / SKD-20KB23 / SKD-20KB32 / SKD-20KB32H

Specification

Model	SKD-20KB21	SKD-20KB23	SKD-20KB32	SKD-20KB32H
CCD	1/4" Sharp CCD	1/3" Sharp CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD
Effective pixels	PAL:512(H)x582(v) NTSC:542(H)x492(v)	PAL:512(H)x582(v) NTSC:542(H)x492(v)	PAL:537(H)x597(V) NTSC:537(H)x505(V)	PAL:537(H)x597(V) NTSC:537(H)x505(V)
Signal System	PAL/NTSC			
Horizontal Resolution	420 TV Lines			450 TV Lines
Lens	3.6mm lens			
Sync. System	Internal			
Minimum Illumination	0.5Lux/F1.2	0.2Lux/F1.2	0.5Lux/F1.2	0.5Lux/F1.2
S/N Ratio	More than 48dB(AGC OFF)			
Electronic Shutter	1/50(1/60)—1/100,000(Sec.)			
White Balance	Auto			
Backlight Compensation	Auto			
Gain Control	Auto			
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)			
Power Sourcing	DC12V ±1V/150mA			
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F) / RH85%(MAX)			