

Fixed Dome Cameras

SKD-20KB34

SKD-20KB35



Features

- SKD-20KB34:
 - 1/3" Sony Super HAD CCD
 - 480 TV Lines / 0.5Lux@F1.2
- SKD-20KB35:
 - 1/3" Sony Exview CCD
 - 480 TV Lines / 0.1Lux@F1.2
- DSP technology
- S/N Ratio more than 48dB
- Build in 3.6mm fixed lens
- BLC and AGC
- Auto White Balance
- DC12V, low consumption

SKD-20KB34 / SKD-20KB35

Specification

Model	SKD-20KB34	SKD-20KB35
CCD	1/3" Sony Super HAD CCD(High Res.)	1/3" Sony Exview CCD
Effective pixels	PAL:752(H)x582(v) NTSC:768(H)x494(v)	PAL:752(H)x582(v) NTSC:768(H)x494(v)
Signal System	PAL/NTSC	
Horizontal Resolution	480 TV Lines	
Lens	3.6mm Lens	
Sync. System	Internal Synchronization	
Minimum Illumination	0.5Lux@F1.2	0.1Lux@F1.2
S/N Ratio	More than 48dB	
Electronic Shutter	1/50(1/60)—1/100,000(Sec.)	
White Balance	Auto	
Backlight Compensation	Auto	
Gain Control	Auto	
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)	
Power Sourcing	DC12V/120mA	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F) / RH95%(MAX)	