

Varifocal Dome Cameras

SKD-22D432

SKD-22D434

SKD-22D435



► Features

- SKD-22D432: 1/3" SONY CCD
420 TV Lines / 0.8Lux@F1.4
 - SKD-22D434: 1/3" SONY Super HAD CCD
480 TV Lines / 1.0Lux@F1.2
 - SKD-22D435: 1/3" SONY Exview CCD
480 TV Lines / 0.2Lux@F1.2
 - BLC, AGC, AWB
 - Build in 3.5-8.0 mm Manual Iris
- Lens
- DC12V, low consumption

SKD-22D432 / SKD-22D434 / SKD-22D435

► Specification

Model	SKD-22D432	SKD-22D434	SKD-22D435
CCD	1/3" Sony CCD	1/3" Sony Super HAD CCD	1/3" Sony Exview CCD
Effective pixels	PAL:500(H)x582(v) NTSC:510(H)x492(v)	PAL:752(H)x582(v) NTSC:768(H)x494(v)	PAL:752(H)x582(v) NTSC:768(H)x494(v)
Signal System	PAL/NTSC		
Horizontal Resolution	420 TV Lines	480 TV Lines	480 TV Lines
Lens	3.5-8.0mm Manual Iris Lens		
Minimum Illumination	0.8Lux@F1.2	1.0Lux@F1.2	0.2Lux@F1.2
S/N Ratio	>48dB	>50dB	>50dB
Electronic Shutter	1/50(1/60)—1/100,000(Sec.)		
White Balance	ON		
Backlight Compensation	ON		
Auto Gain Control	ON		
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)		
Power Sourcing	DC12V		
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F) RH95%(MAX)		
Weight	380g		
Dimension	128mm (Dia.) * 90mm (H)		

► Dimension

