

3 Axis Color Domes



► Features

- 3 Axis Dome
- High Resolution 420 TVL
- 0.5 LUX
- Built-in 4-9mm Motorized Lens
- With Remote Control(RS485) Optional



SKD-22MF521 / SKD-22MF532

► Specification

Model	SKD-22MF521	SKD-22MF532
CCD	1/4" Sharp Color CCD Sensor	1/3" Sony Super HAD CCD
Effective pixels	NTSC: 512(H) x 492(V) PAL: 512 (H) x 582(V)	NTSC: 537(H)x505(V) PAL: 537(H)x597(V)
Signal System	NTSC/PAL	
Horizontal Resolution	420 TV Lines	420 TV Lines
Lens	4-9mm Motorized Lens	
Sync. System	Inter line Synchronization	
Minimum Illumination	1LUX	0.5LUX
S/N Ratio	More than 48dB (AGC off)	
Electronic Shutter	PAL: 1/50~1/100,000 sec	
White balance	Auto White Balance(AWB)	
BLC	Back Light Compensation (Auto)	
IR Distance	-	
Infrared Led	-	
Video Output	Composite Video Output(1.0Vp-p 75ΩTerminated)	
Power Sourcing	DC12V 150mA	
Operating Temperature	-10~+50°C RH95%Max	