

Vandal Resistant Dome Cameras

SKD-24C321

SKD-24C332

SKD-24C334



Features

- SKD-24C321:
 - 1/4" SHARP CCD
 - 420 TV Lines / 1.0Lux@F1.2
- SKD-24C332 :
 - 1/3" SONY SUPER HAD CCD
 - 420 TV Lines / 0.5Lux@F1.2
- SKD-24C334 :
 - 1/3" SONY SUPER HAD CCD
 - 480 TV Lines / 0.8Lux@F1.2
 - DSP technology
 - BLC, AES, AGC, AWB
- Built-in 3.6mm Lens, excellent Value
- DC12V/130mA

SKD-24C321 / SKD-24C332 / SKD-24C334

Specification

| Model | SKD-24C321 | SKD-24C332 | SKD-24C334 |
|------------------------|---|---|---|
| CCD | 1/4" SHARP CCD | 1/3" SONY SUPER HAD CCD | 1/3" SONY SUPER HAD CCD |
| Effective pixels | PAL:512(H)x582(v) NTSC:512(H)x492(v) | PAL:500(H)x582(v) NTSC:510(H)x492(v) | PAL:752(H)x582(v) NTSC:768(H)x494(v) |
| Signal System | PAL/NTSC | | |
| Horizontal Resolution | 420 TV Lines | 420 TV Lines | 480 TV Lines |
| Lens | 3.6mm lens | | |
| Sync. System | Internal | | |
| Minimum Illumination | 1.0Lux @F1.2 | 0.5Lux @F1.2 | 0.8Lux @F1.2 |
| S/N Ratio | More than 48dB(AGC OFF) | | |
| Electronic Shutter | 1/50(1/60)—1/100,000(Sec.) | | |
| White Balance | ATW | | |
| Backlight Compensation | Auto | | |
| Auto Gain Control | Auto | | |
| Video Output | Composite Video Output(1Vp-p 75ΩTerminated) | | |
| Power Sourcing | DC12V ±1V/120mA | | |
| Operating Temperature | -10°C ~ 50°C (14°F ~ 122°F) RH95%(MAX) | | |
| Weight | 1.65 kg | | |
| Dimension | 155mm (Dia.) * 115mm (H) | | |

Dimension

